

IOC/2008/TS/85 Original: English

The designations employed and the presentation of the material in this publication do not imply the expression of any opinion whatsoever on the part of the Secretariats of UNESCO and IOC concerning the legal status of any country or territory, or its authorities, or concerning the delimitation of the frontiers of any country or territory.

#### For bibliographic purposes, this document should be cited as follows:

Intergovernmental Oceanographic Commission. 2008. *Tsunami Glossary, 2008.* Paris, UNESCO. IOC Technical Series, 85. (English.)

Published by the United Nations Educational, Scientific and Cultural Organization 7 Place de Fontenoy, 75 352 Paris 07 SP, France

Printed by the U.S. National Oceanic and Atmospheric Administration (NOAA) The International Tsunami Information Center, 737 Bishop St., Ste. 2200, Honolulu, Hawaii 96813, U.S.A.



Photo courtesy of Bishop Museum Archives.

# 1 TSUNAMI CLASSIFICATION

### CHARACTERISTICS OF THE TSUNAMI PHENOMENA

A tsunami travels outward from the source region as a series of waves. Its speed depends upon the depth of the water, and consequently the waves undergo accelerations or decelerations in passing respectively over an ocean bottom of increasing or decreasing depth. By this process the direction of wave propagation also changes, and the wave energy can become focused or defocused. In the deep ocean, tsunami waves can travel at speeds of 500 to 1,000 kilometres (km) per hour. Near the shore, however, a tsunami slows down to just a few tens of kilometres per hour. The height of a tsunami also depends upon the water depth. A tsunami that is just a metre in height in the deep ocean can grow to tens of metres at the shoreline. Unlike familiar wind-driven ocean waves that are only a disturbance of the sea surface, the tsunami wave energy extends to the ocean bottom. Near the shore, this energy is concentrated in the vertical direction by the reduction in water depth, and in the horizontal direction by a shortening of the wavelength due to the wave slowing down.

Tsunamis have periods (the time for a single wave cycle) that may range from just a few minutes to as much as an hour or exceptionally more. At the shore, a tsunami can have a wide variety of expressions depending on the size and period of the waves, the near-shore bathymetry and shape of the coastline, the state of the tide, and other factors. In some cases a tsunami may only induce a relatively benign flooding of lowlying coastal areas, coming onshore similar to a rapidly rising tide. In other cases it can come onshore as a bore - a vertical wall of turbulent water full of debris that can be very destructive. In most cases there is also a drawdown of sea level preceding crests of the tsunami waves that result in a receding of the waterline, sometimes by a kilometre or more. Strong and unusual ocean currents may also accompany even small tsunamis.

Damage and destruction from tsunamis is the direct result of three factors: inundation, wave impact on structures, and erosion. Deaths occur by drowning and physical impact or other trauma when people are caught in the turbulent, debrisladen tsunami waves. Strong tsunami-induced currents have led to the erosion of foundations and the collapse of bridges and seawalls. Floatation and drag forces have moved houses and overturned railroad cars. Tsunami associated wave forces have demolished frame buildings and other structures. Considerable damage also is caused by floating debris, including boats, cars, and trees that become dangerous projectiles that may crash into buildings, piers, and other vehicles. Ships and port facilities have been damaged by surge action caused by even weak tsunamis. Fires resulting from oil spills or combustion from damaged ships in port, or from ruptured coastal oil storage and refinery facilities, can cause damage greater than



that inflicted directly by the tsunami. Other secondary damage can result from sewage and chemical pollution following the destruction. Damage of intake, discharge, and storage facilities also can present dangerous problems. Of increasing concern is the potential effect of tsunami drawdown, when receding waters uncover cooling water intakes associated with nuclear power plants.

### HISTORICAL TSUNAMI

A tsunami documented to occur through eyewitness or instrumental observation within the historical record.

### **LOCAL TSUNAMI**

A tsunami from a nearby source for which its destructive effects are confined to coasts within about 100 km (or, alternatively, less than 1 hour travel tsunami travel time) from its source. Alocal tsunami is usually generated by an earthquake, but can also be caused by a landslide or a pyroclastic flow from a volcanic eruption.

### Maremoto

Spanish term for tsunami.



Damage caused by the 22 May 1960 Chilean tsunami. Photo courtesy of Ilustre Municipalidad de Maullin, USGS Circular 1187.

### Meteorological tsunami (meteotsunami)

Tsunami-like phenomena generated by meteorological or atmospheric disturbances. These waves can be produced by atmospheric gravity waves, pressure jumps, frontal passages, squalls, gales, typhoons, hurricanes and other atmospheric sources. Meteotsunamis have the same temporal and spatial scales as tsunami waves and can similarly devastate coastal areas, especially in bays and inlets with strong amplification and well-defined resonant properties (e.g. Ciutadella Inlet, Baleric Islands; Nagasaki Bay, Japan; Longkou Harbour, China; Vela Luka, Stari Grad and Mali Ston Bays, Croatia). Sometimes referred to as *rissaga*.

#### **MICROTSUNAMI**

A tsunami of such small amplitude that it must be observed instrumentally and is not easily detected visually.

#### **O**CEAN-WIDE TSUNAMI

A tsunami capable of widespread destruction, not only in the immediate region of its generation but across an entire ocean. All ocean-wide tsunamis have been generated by major earthquakes. Synonym for teletsunami or distant tsunami.

### Paleotsunami

Tsunami occurring prior to the historical record or for which there are no written observations. Paleotsunami research is based primarily on the identification, mapping, and dating of tsunami deposits found in coastal areas, and their correlation with similar sediments found elsewhere locally, regionally, or across ocean basins. In one instance, the research has led to a new concern for the possible future occurrence of



Numerical modelling snapshots of the water surface 10 minutes after a pyroclastic flow on the southeastern part of Monserrat Island led to a submarine landslide and the generation of a tsunami. Courtesy of LDG-France.











The four images above show tsunami source locations in the Pacific Ocean, Indian Ocean, Mediterranean Sea, and Caribbean Sea. The symbols indicate cause of the tsunami: ■ is a landslide, ▲ is a volcanic eruption, ? is an unknown cause, and ○ is an earthquake and the size of the circle is graduated to indicate the earthquake magnitude. Source: National Geophysical Data Center / World Data Center.

## Regional and Local Tsunamis causing 2,000 or more deaths

				Estimated Dead or
Date			Source Location	Missing
365	7	21	Crete, Greece	5,700
887	8	2	Niigata, Japan	2,000
1341	10	31	Aomori Prefecture, Japan	2,600
1498	9	20	Enshunada Sea, Japan	31,000
1570	2	8	Central Chile	2,000
1586	1	18	lse Bay, Japan	8,000
1605	2	3	Nankaido, Japan	5,000
1611	12	2	Sanriku, Japan	5,000
1674	2	17	Banda Sea, Indonesia	2,243
1687	10	20	Southern Peru	*5,000
1692	6	7	Port Royal, Jamaica	2,000
1703	12	30	Boso Peninsula, Japan	*5,233
1707	10	28	Enshunada Sea, Japan	2,000
1707	10	28	Nankaido, Japan	30,000
1746	10	29	Central Peru	4,800
1751	5	20	Northwest Honshu, Japan	2,100
1755	11	1	Lisbon, Portugal	*60,000
1771	4	24	Ryukyu Islands, Japan	13,486
1783	2	5	Strait of Messina, Italy	*30,000
1792	5	21	Kyushu Island, Japan**	4,300
1854	12	24	Nankaido, Japan	*3,000
1883	8	27	Krakatau, Indonesia**	36,000
1896	6	15	Sanriku, Japan	*27,122
1899	9	29	Banda Sea, Indonesia	*2,460
1923	9	1	Sagami Bay, Japan	2,144
1933	3	2	Sanriku, Japan	3,022
1941	6	26	Andaman Sea, India	5,000
1976	8	16	Moro Gulf, Philippines	4,456
1992	12	12	Flores Sea, Indonesia	*2500
1998	7	17	Papua New Guinea	2,183
2004	12	26	Banda Aceh, Indonesia	*227,898

\* May include earthquake casualties \*\* Tsunami generated by volcanic eruption

great earthquakes and tsunamis along the northwest coast of North America. In another instance, the record of tsunamis in the Kuril-Kamchatka region is being extended much further back in time. As work in this field continues it may provide a significant amount of new information about past tsunamis to aid in the assessment of the tsunami hazard.



#### Regional and Local Tsunamis causing deaths since 1975

			Ē	stimated
Date			Source Location	Dead or Missing
4075	40	24		1
1975	10	31	Philippine Trench Hawaii, USA	2
1975	11	29		2 4,456
1976	8	16	Moro Bay, Philippines	
1977	8	19	Sumbawa, Indonesia	189
1979	7	18	Lebata Island, Indonesia**	539
1979	9	12	Irian Jaya, Indonesia	100
1979	10	16	French Riveria**	6
1979	12	12	Narino, Colombia	*600
1981	9	1	Samoa Islands	2
1983	5	26	Noshiro, Japan	100
1988	8	10	Solomon Islands	1
1991	4	22	Limon, Costa Rica	2
1992	9	2	Off coast Nicaragua	170
1992	12	12	Flores Sea, Indonesia	*2,500
1993	7	12	Sea of Japan	330
1994	2	15	Sumatra, Indonesia	7
1994	6	2	Java, Indonesia	250
1994	10	8	Halmahera, Indonesia	1
1994	11	4	Skagway Alaska, USA**	1
1994	11	14	Philippine Islands	*78
1995	5	14	Timor, Indonesia	11
1995	10	9	Manzanillo, Mexico	1
1996	1	1	Sulawesi, Indonesia	9
1996	2	17	Irian Jaya, Indonesia	110
1996	2	21	Northern Peru	12
1998	7	17	Papua New Guinea	2,183
1999	8	17	Izmit Bay, Turkey	150
1999	11	26	Vanuatu Islands	5
2001	6	23	Southern Peru	26
2005	3	28	Sumatra, Indonesia	10
2006	3	14	Seram Island, Indonesia	4
2006	7	17	Java, Indonesia	664
2007	4	1	Solomon Islands	*52
2007	4	21	Southern Chile	10

\* May include earthquake casualties \*\* Tsunami generated by landslide

### **REGIONAL TSUNAMI**

A tsunami capable of destruction in a particular geographic region, generally within 1,000 km or 1-3 hours tsunami travel time from its source. Regional tsunamis also occasionally have very limited and localized effects outside the region.

Most destructive tsunami can be classified as









More than 80% of the world's tsunamis were caused by earthquakes and over 60% of these were observed in the Pacific where large earthquakes occur as tectonic plates are subducted along the Pacific Ring of Fire. Top: Epicentre of all tsunamigenic earthquakes. Tsunamis have caused damage locally in all ocean basins. Middle: Locations of earthquakes, volcanic eruptions, and landslides generating tsunamis that caused damage or casualties locally. Although the majority of tsunamis that were observed more than 1,000 km away (teletsunamis) were generated by earthquakes in the Pacific, teletsunamis have also caused damage and casualties in the Indian and Atlantic oceans. Bottom: Source locations of teletsunamis causing damage or casualties. These data are based on historical records. Source: National Geophysical Data Center/World Data Center.

local or regional. It follows many tsunami related casualties and considerable property damage also comes from these tsunamis. Between 1975 and 2007 there were 34 local or regional tsunamis that resulted in deaths and property damage; 23 of these were in the Pacific and adjacent seas.

For example, a regional tsunami in 1983 in the Sea of Japan or East Sea, severely damaged

coastal areas of Japan, Korea, and Russia, causing more than \$800 million in damage, and more than 100 deaths. Then, after nine years with only one event causing one fatality, 11 locally destructive tsunamis occurred in just a sevenyear period from 1992 to 1998, resulting in over 5,300 deaths and hundreds of millions of dollars in property damage. In most of these cases, tsunami mitigation efforts in place at the time were unable to prevent significant damage and loss of life. However, losses from future local or regional tsunamis can be reduced if a denser network of warning centres, seismic and water-level reporting stations, and better communications are established to provide a timely warning, and if better programs of tsunami preparedness and education can be put in place.

### **TELETSUNAMI OR DISTANT TSUNAMI**

A tsunami originating from a far away source, generally more than 1,000 km or more than 3 hours tsunami travel time from its source.

Less frequent, but more hazardous than regional tsunamis, are ocean-wide or distant tsunamis. Usually starting as a local tsunami that causes extensive destruction near the source, these waves continue to travel across an entire ocean basin with sufficient energy to cause additional casualties and destruction on shores. In the last 200 years, there have been at least 26 destructive ocean-wide tsunamis and 9 caused fatalities more than 1,000 kilometres from the source.

The most destructive Pacific-wide tsunami of recent history was generated by a massive earthquake off the coast of Chile on 22 May 1960. All Chilean coastal towns between the 36th and 44th parallels were either destroyed or heavily damaged by the action of the tsunami and the earthquake. The combined tsunami and earthquake toll included 2,000 killed, 3,000 injured, two million homeless, and \$550 million damage. Off the coast of Corral, Chile, the waves were estimated to be 20 metres (67 feet) high. The tsunami caused 61 deaths in Hawaii, 20 in the Philippines, and 139 in Japan. Estimated damages were US \$50 million in Japan, US \$24 million in Hawaii and several millions of dollars along the west coast of the United States and Canada. Distant wave heights varied from slight oscillations in some areas to 12 metres (40 feet) at Pitcairn Island, 11 metres at Hilo, Hawaii, and six metres at some places in Japan.

The worst tsunami catastrophe in history occurred in the Indian Ocean on 26 December 2004, when a M9.3 earthquake off of the northwest coast of Sumatra, Indonesia produced a ocean-wide tsunami that hit Thailand and Malaysia to the east, and Sri Lanka, India, the Maldives, and Africa to the west as it traversed across the Indian Ocean. Nearly 228,000 people lost their lives and more than a million people were displaced, losing their homes, property, and their livelihoods. The magnitude of death and destructiveness caused immediate response by

					ated Dead Missing	
Date			Earthquake Location	Local	Distant	Distant locations that reported casualties
1837	11	7	Southern Chile	0	16	USA (Hawaii)
1868	8	13	Northern Chile	25,000*	1	New Zealand, Southern Chile
1877	5	10	Northern Chile	Hundreds	Thousands	Fiji, Japan, Peru, USA (Hawaii)
1923	2	3	Kamchatka, Russia	2	1	USA (Hawaii)
1945	11	27	Makran coast, Pakistan	300*	Some	India
1946	4	1	Unimak Island, Alaska, USA	5	160	USA (California, Hawaii)
1960	5	22	Central Chile	1,000	283	Japan, Philippines, USA (California, Hawaii)
1964	3	28	Prince William Sound, Alaska, USA	106	18	USA (California, Oregon)
2004	12	26	Banda Aceh, Indonesia	175,827*	52,071	Bangladesh, India, Kenya, Maldives, Myanmar, Seychelles, Somalia, South Africa, Sri Lanka, Tanzania, Yemen

\* May include earthquake casualties



the world's leaders and led to the development of the Indian Ocean tsunami warning and mitigation system in 2005. The event also raised awareness of tsunami hazards globally, and new systems were established in the Caribbean, the Mediterranean and Atlantic.



The tsunami of 26 December 2004 destroyed the nearby city of Banda Aceh leaving only a few structures standing. Photo courtesy of Yuichi Nishimura, Hokkaido University.

### TSUNAMI

Japanese term meaning wave ("nami") in a harbour ("tsu"). A series of traveling waves of extremely long length and period, usually generated by disturbances associated with earthquakes occurring below or near the ocean floor. (Also called seismic sea wave and, incorrectly, tidal wave). Volcanic eruptions, submarine landslides, and coastal rockfalls can also generate tsunamis, as can a large meteorite impacting the ocean. These waves may reach enormous dimensions and travel across entire ocean basins with little loss of energy. They proceed as ordinary gravity waves with a typical period between 10 and 60 minutes. Tsunamis steepen and increase in height on approaching shallow water, inundating low-lying areas, and where local submarine topography causes the waves to steepen, they may break and cause great damage. Tsunamis have no connection with tides; the popular name, tidal wave, is entirely misleading.



Destruction along the waterfront of Hilo, Hawaii from the Pacific-wide tsunami generated off the coast of Unimak Island, Aleutian Island, USA on 1 April 1946.



Tsunami generated by 26 May 1983, Japan Sea earthquake approaching Okushiri Island, Japan. Photo courtesy of Tokai University.

### **T**SUNAMI EARTHQUAKE

An earthquake that produces an unusually large tsunami relative to the earthquake magnitude (Kanamori,1972). Typical characteristics of tsunami earthquakes include long rupture durations for the magnitude of the earthquake, rupture on the very shallow part of the plate interface (inferred from a location near the trench and a low-angle thrust mechanism), and high energy release at low frequencies. They are also slow earthquakes, with slippage along their faults occurring more slowly than would occur in normal earthquakes. The last events of this type were in 1992 (Nicaragua), 1994 (Java), 1996 (Chimbote, Peru) and 2006 (Java).

#### **T**SUNAMI SEDIMENTS

Sediments deposited by a tsunami. The finding of tsunami sediment deposits within the stratigraphic soil layers provides information on the occurrence of historical and paleotsunamis. The discovery of similarly-dated deposits at different locations, sometimes across ocean basins and far from the tsunami source, can be used to map and infer the distribution of tsunami inundation and impact.



Sediment layers deposited from successive waves of 26 December 2004 Indian Ocean tsunami, as observed in Banda Aceh, Indonesia. Photo courtesy of Yuichi Nishimura, Hokkaido University.





This section contains general terms used in tsunami mitigation and in tsunami generation and modelling.

### Breaker

A sea-surface wave that has become so steep (wave steepness of 1/7) that the crest outraces the body of the wave and it collapses into a turbulent mass on shore or over a reef. Breaking usually occurs when the water depth is less than 1.28 times the wave height. Roughly, three kinds of breakers can be distinguished, depending primarily on the gradient of the bottom: a) spilling breakers (over nearly flat bottoms) which form a foamy patch at the crest and break gradually over a considerable distance; b) plunging breakers (over fairly steep bottom gradients) which peak up, curl over with a tremendous overhanging mass and then break with a crash; c) surging breakers (over very steep bottom gradients) which do not spill or plunge but surge up the beach face. Waves also break in deep water if they build too high while being generated by the wind, but these are usually short-crested and are termed whitecaps.

### Breakwater

An offshore or onshore structure, such as a wall, water gate, or other in-water wave-dissipating object that is used to protect a harbour or beach from the force of waves.



Sea wall with stairway evacuation route used to protect a coastal town against tsunami inundation in Japan. Photo courtesy of River Bureau, Ministry of Land, Infrastructure and Transport, Japan.



Water gate used to protect against tsunami waves on Okushiri Island, Japan. The gate begins to automatically close within seconds after earthquake shaking triggers its seismic sensors. Photo courtesy of ITIC.

### Eddy

By analogy with a molecule, a "glob" of fluid within the fluid mass that has a certain integrity and life history of its own; the activities of the bulk fluid being the net result of the motion of the eddies.



Eddies generated by the interactions of tsunami waves as they hit the coast of Sri Lanka, 26 December 2004. Photo courtesy of Digital Globe.



### **ESTIMATED TIME OF ARRIVAL (ETA)**

Time of tsunami arrival at some fixed location, as estimated from modelling the speed and refraction of the tsunami waves as they travel from the source. ETA is estimated with very good precision if the bathymetry and source are well known (less than a couple of minutes). The first wave is not necessarily the largest, but it is usually one of the first five waves.

### **EVACUATION MAP**

A drawing or representation that outlines danger zones and designates limits beyond which people must be evacuated to avoid harm from tsunami waves. Evacuation routes are sometimes designated to ensure the efficient movement of people out of the evacuation zone to evacuation shelters.



Inundation and Evacuation Map created for the coastal town of Pucusana, Peru.



Elevated platform used for tsunami evacuation that also serves as a high-elevation scenic vista point for tourist. Okushiri Island, Japan. Photo courtesy of ITIC.



Emergency shelter building that also acts as community centre and Museum for Disaster Prevention. Kisei, Mie Prefecture, Japan. The building is 22-m high, has five floors covering 320 m<sup>2</sup>, and holds 500 persons. Info courtesy of http://www.webmie.or.jp.

### HISTORICAL TSUNAMI DATA

Historical data are available in many forms and at many locations. These forms include published and unpublished catalogs of tsunami occurrences, personal narratives, marigraphs, tsunami amplitude, runup and inundation zone measurements, field investigation reports, newspaper accounts, film, or video records.

### SEICHE

A seiche may be initiated by a standing wave oscillating in a partially or fully enclosed body of water. It may be initiated by long period seismic waves (an earthquake), wind and water waves, or a tsunami.

### **S**EISMIC SEA WAVE

Tsunamis are sometimes referred to as seismic sea waves because they are most often generated by earthquakes.

#### **TRAVEL TIME**

Time required for the first tsunami wave to propagate from its source to a given point on a coastline.

### **TRAVEL TIME MAP**

Map showing isochrons or lines of equal tsunami travel time calculated from the source outwards toward terminal points on distant coastlines.



Travel times (in hours) for the 22 May 1960 Chile tsunami crossing the Pacific basin. This tsunami was extremely destructive along the nearby coast of Chile, and the tsunami also caused significant destruction and casualties as far away as Hawaii and Japan. The awareness and concern raised by this Pacific-wide tsunami ultimately led to the formation of the PTWS.

### **T**SUNAMI BORE

A steep, turbulent, rapidly moving tsunami wave front, typically occurring in a river mouth or estuary.



Tsunami bore entering Wailua River, Hawaii during the 1946 Aleutian Island tsunami. Photo courtesy of Pacific Tsunami Museum.

#### **T**SUNAMI DAMAGE

Loss or harm caused by a destructive tsunami. More specifically, the damage caused directly by tsunamis can be summarized into the following: 1) deaths and injuries; 2) houses destroyed, partially destroyed, inundated, flooded, or burned; 3) other property damage and loss; 4) boats washed away, damaged or destroyed; 5) lumber washed away; 6) marine installations destroyed, and; 7) damage to public utilities such as railroads, roads, electric power plants, water supply installations, etc. Indirect secondary tsunami damage can be: 1) Damage by fire of houses, boats, oil tanks, gas stations, and other facilities; 2) environmental pollution caused by drifting materials, oil, or other substances; 3) outbreak of disease of epidemic proportions, which could be serious in densely populated areas.



Massive destruction in the town of Aonae on Okushiri Island, Japan caused by the regional tsunami of 12 July 1993. Photo courtesy of Dr. Eddie Bernard, NOAA PMEL





Banda Aceh, Sumatra, Indonesia. The tsunami of 26 December 2004 completely razed coastal towns and villages, leaving behind only sand, mud, and water where once there had been thriving communities of homes, offices, and green space. Photo courtesy of Digital Globe.



### **TSUNAMI DISPERSION**

Redistribution of tsunami energy, particularly as a function of its period, as it travels across a body of water.

### **TSUNAMI EDGE WAVE**

Wave generated by a tsunami that travels along the coast.

### **TSUNAMI FORERUNNER**

A series of oscillations of the water level preceding the arrival of the main waves.

### **TSUNAMI GENERATION**

Tsunamis are most frequently caused by earthquakes, but can also result from landslides, volcanic eruptions, and very infrequently by meteorites or other impacts upon the ocean surface. Tsunamis are generated primarily by tectonic dislocations under the sea which are caused by shallow focus earthquakes along areas of subduction. The upthrusted and downthrusted crustal blocks impart potential energy into the overlying water mass with drastic changes in the sea level over the affected region. The energy imparted into the water mass results in tsunami generation, i.e. energy radiating away from the source region in the form of long period waves.



Tsunamis can be generated by submarine landslides, or by subaerial landslides that enter the water. Courtesy of LDG-France.



Most tsunamis are generated by large, shallow, thrust earthquakes that occur as a tectonic plate is subducted. Shallow earthquakes also occur along spreading ridges, but these are not large enough to cause tsunamis. Large, shallow earthquakes also occur along transform faults, but there is only minor vertical motion during the faulting so no tsunamis are generated.



Tsunamis are most often generated by shallow earthquakes.





Tsunamis can be generated by pyroclastic flows associated with volcanic eruptions. Courtesy of LDG-France.

### **T**SUNAMI GENERATION THEORY

The theoretical problem of generation of the gravity wave (tsunami) in the layer of elastic liquid (an ocean) occurring on the surface of elastic solid half-space (the crust) in the gravity field can be studied with methods developed in the dynamic theory of elasticity.

The source representing an earthquake focus is a discontinuity in the tangent component of the displacement on some element of area within the crust. For conditions representative of the Earth's oceans, the solution of the problem differs very little from the joint solution of two more simple problems: the problem of generation of the displacement field by the given source in the solid elastic half-space with the free boundary (the bottom) considered guasi-static and the problem of the propagation of gravity wave in the layer of heavy incompressible liquid generated by the known (from the solution of the previous problem) motion of the solid bottom. There is the theoretical dependence of the gravity wave parameters on the source parameters (depth and orientation). One can roughly estimate the quantity of energy transferred to the gravity wave by the source. In general, it corresponds to the estimates obtained with empirical data. Also, tsunamis can be generated by other different mechanisms such as volcanic or nuclear explosions, landslides, rock falls, and submarine slumps.

#### **T**SUNAMI HAZARD

The probability that a tsunami of a particular size will strike a particular section of coast.



Global tsunami source zones. Tsunami hazards exist in all oceans and basins, but occur most frequently in the Pacific Ocean. Tsunamis can occur anywhere and at any time because earthquakes cannot be accurately predicted. Courtesy of LDG-France.

### **T**SUNAMI HAZARD ASSESSMENT

Documentation of tsunami hazards for a coastal community is needed to identify populations and assets at risk, and the level of that risk. This assessment requires knowledge of probable tsunami sources (such as earthquakes, landslides, and volcanic eruptions), their likelihood of occurrence, and the characteristics of tsunamis from those sources at different places along the coast. For those communities, data of earlier (historical and paleotsunamis) tsunamis may help quantify these factors. For most communities, however, only very limited or no past data exist. For these coasts, numerical models of tsunami inundation can provide estimates of areas that will be flooded in the event of a local or distant tsunamigenic earthquake or a local landslide.

### **T**SUNAMI IMPACT

Although infrequent, tsunamis are among the most terrifying and complex physical phenomena and have been responsible for great loss of life and extensive destruction to property. Because of their destructiveness, tsunamis have important impacts on the human, social, and economic sectors of societies. Historical records show that enormous destruction of coastal communities throughout the world has taken place and that the socio-economic impact of tsunamis in the past has been enormous. In the Pacific Ocean where the majority of these waves have been generated, the historic record shows tremendous destruction with extensive loss of life and property.

In Japan, which has one of the most populated coastal regions in the world and a long history of earthquake activity, tsunamis have destroyed entire coastal populations. There is also a history of severe tsunami destruction in Alaska, the Hawaiian Islands, and South America, although records for these areas are not as extensive. The last major Pacific-wide tsunami occurred in 1960. Many other local and regional destructive tsunamis have occurred with more localized effects.



Estimated tsunami inundation at Iquique, Chile, based on numerical model results. Courtesy of SHOA - Chile.

### **T**SUNAMI NUMERICAL MODELLING

Mathematical descriptions that seek to describe the observed tsunami and its effects.

Often the only way to determine the potential runups and inundation from a local or distant tsunami is to use numerical modelling, since data from past tsunamis is usually insufficient. Models can be initialized with potential worst case scenarios for the tsunami sources or for the waves just offshore to determine corresponding worst case scenarios for runup and inundation. Models can also be initialized with smaller sources to understand the severity of the hazard for the less extreme but more frequent events. This information is then the basis for creating tsunami evacuation maps and procedures. At present, such modelling has only been carried out for a small fraction of the coastal areas at risk. Sufficiently accurate modelling techniques have only been available in recent years, and these models require training to understand and use correctly, as well as input of detailed bathymetric and topographic data in the area being modeled.

Numerical models have been used in recent years to simulate tsunami propagation and interaction with land masses. Such models usually solve similar equations but often employ different numerical techniques and are applied to different segments of the total problem of tsunami propagation from generation regions to distant areas of runup. For example, several numerical models have been used to simulate the interaction of tsunamis with islands. These models have used finite difference, finite element, and boundary integral methods to solve the linear long wave equations. These models solve these relatively simple equations and provide reasonable simulations of tsunamis for engineering purposes.

Historical data are often very limited for most coastlines. Consequently, numerical modelling may be the only way to estimate potential risk. Techniques now exist to carry out this assessment. Computer software and the training necessary to conduct this modelling are available through programmes such as the IOC Tsunami Inundation Modelling Exchange (TIME) Programme.



Calculated maximum tsunami wave heights for a M9.0 Cascadia subduction zone earthquake. The model was calculated after tsunami deposits found in Japan and elsewhere suggested that a repeat of the 1700 Cascadia great earthquake would generate a destructive teletsunami. Courtesy of Kenji Satake, Geological Survey of Japan.







### **TSUNAMI OBSERVATION**

Notice, observation or measurement of sea level fluctuation at a particular point in time caused by the incidence of a tsunami on a specific point.



1946 Aleutian Islands tsunami rushing ashore in Hilo, Hawaii. Photo courtesy of Pacific Tsunami Museum.

### **TSUNAMI PREPAREDNESS**

Readiness of plans, methods, procedures and actions taken by government officials and the general public for the purpose of minimizing potential risk and mitigating the effects of future tsunamis. The appropriate preparedness for a warning of impending danger from a tsunami requires knowledge of areas that could be flooded (tsunami inundation maps) and knowledge of the warning system to know when to evacuate and when it is safe to return.



Complex numerical model calculated to match the 1958 Lituya Bay, Alaska landslide-generated local tsunami which caused the largest runup ever recorded (525 m). The complex model matches very closely the detail of the second order eddies and splash effects that laboratory experiments showed. Courtesy of Galen Gisler, Los Alamos National Laboratory.



Tsunami hazard sign approved by International Standards Organization (ISO).





Tsunami evacuation route sign, Chile.



Tsunami evacuation building and safe place signs, Japan.



IN CASE OF EARTHQUAKE, GO TO HIGH GROUND OR INLAND

Tsunami hazard zone sign, Washington, USA.

### **T**SUNAMI PROPAGATION

Tsunamis travel outward in all directions from the generating area, with the direction of the main energy propagation generally being orthogonal to the direction of the earthquake fracture zone. Their speed depends on the depth of water, so that the waves undergo accelerations and decelerations in passing over an ocean bottom of varying depth. In the deep and open ocean, they travel at speeds of 500 to 1,000 km per hour (300 to 600 miles per hour). The distance between successive crests can be as much as 500 to 650 km (300 to 400 miles). However, in the open ocean, the height of the waves is generally less than a metre (three feet) even for the most destructive teletsunamis, and the waves pass unnoticed. Variations in tsunami propagation result when the propagation impulse is stronger in one direction than in others because of the orientation or dimensions of the generating area and where regional bathymetric and topographic features modify both the waveform and rate of advance. Specifically, tsunami waves undergo a process of wave refraction and reflection throughout their travel. Tsunamis are unique in that the energy extends through the entire water column from sea surface to the ocean bottom. It is this characteristic that accounts for the great amount of energy propagated by a tsunami.



Model of tsunami propagation in the southeast Pacific, nine hours after generation. Source: Antofagasta, Chile (30 July 1995). Courtesy of LDG-France.



#### **T**SUNAMI RESONANCE

The continued reflection and interference of tsunami waves from the edge of a harbour or narrow bay which can cause amplification of the wave heights, and extend the duration of wave activity from a tsunami.

#### **T**SUNAMI RISK

The probability of a particular coastline being struck by a tsunami multiplied by the likely destructive effects of the tsunami and by the number of potential victims. In general terms, risk is the hazard multiplied by the exposure.

#### **T**SUNAMI SIMULATION

Numerical model of tsunami generation, propagation, and inundation.

### **TSUNAMI SOURCE**

Point or area of tsunami origin, usually the site of an earthquake, volcanic eruption, or landslide that caused large-scale rapid displacement of the water to initiate the tsunami waves.



Wave height and water depth. In the open ocean, a tsunami is often only a tens of centimeters high, but its wave height grows rapidly in shallow water. Tsunami wave energy extends from the surface to the bottom in the deepest waters. As the tsunami attacks the coastline, the wave energy is compressed into a much shorter distance creating destructive, life threatening waves.

### TSUNAMI VELOCITY OR Shallow water velocity

The velocity of an ocean wave whose length is sufficiently large compared to the water depth

(i.e., 25 or more times the depth) can be approximated by the following expression:

$$c = \sqrt{(gh)}$$

Where:

c: is the wave velocity

g: the acceleration of gravity

h: the water depth.

Thus, the velocity of shallow-water waves is independent of wave length L. In water depths between  $\frac{1}{2}$  L and  $\frac{1}{25}$  L it is necessary to use a more precise expression:

$$c = \sqrt{((gL/2\pi)[tanh(2\pi h/L)])}$$

### TSUNAMI ZONATION (TSUNAMI ZONING)

Designation of distinctive zones along coastal areas with varying degrees of tsunami risk and vulnerability for the purpose of disaster preparedness, planning, construction codes, or public evacuation.

### TSUNAMIC

Having features analogous to those of a tsunami or descriptive of a tsunami.

#### **T**SUNAMIGENIC

Capable of generating a tsunami. For example: a tsunamigenic earthquake, a tsunamigenic landslide.



Destruction of Hilo Harbor, Hawaii, 1 April 1946. The tsunami generated off the coast of Unimak Island, Aleutian Islands raced across the Pacific, coming ashore in Hawaii less than five hours later. Photo courtesy of NOAA.



# SURVEYS AND MEASUREMENTS

This section contains terms used to measure and describe tsunami waves on mareographs and in the field during a survey, and terms used to describe the size of the tsunami.

### **ARRIVAL TIME**

Time of the first maximum of the tsunami waves.

### **CREST LENGTH**

The length of a wave along its crest. Sometimes called crest width.

### DROP

The downward change or depression in sea level associated with a tsunami, a tide, or some long term climatic effect.

### **ELAPSED TIME**

Time between the maximum level arrival time and the arrival time of the first wave.

### **INITIAL RISE**

Time of the first minimum of the tsunami waves.

### INTENSITY

A measure of strength, force, or energy.



### INUNDATION OR INUNDATION-DISTANCE

The horizontal distance inland that a tsunami penetrates, generally measured perpendicularly to the shoreline.





Tsunami inundation generated by the earthquake of 26 May 1983, at Oga aquarium in Japan. Photo courtesy of Takaaki Uda, Public Works Research Institute, Japan.

### **INUNDATION (MAXIMUM)**

Maximum horizontal penetration of the tsunami from the shoreline. A maximum inundation is measured for each different coast or harbour affected by the tsunami.

### **INUNDATION AREA**

Area flooded with water by the tsunami.





Dark area shows inundation area from the 1964 Alaska tsunami. Photo courtesy of NGDC.

### **INUNDATION LINE**

Inland limit of wetting, measured horizontally from the mean sea level (MSL) line. The line between living and dead vegetation is sometimes used as a reference. In tsunami science, the landward limit of tsunami runup.

### **LEADING WAVE**

First arriving wave of a tsunami. In some cases, the leading wave produces an initial depression or drop in sea level, and in other cases, an elevation or rise in sea level. When a drop in sea level occurs, sea level recession is observed.

### MAGNITUDE

A number assigned to the properties of an event such that the event can be compared to other events of the same class.

### **MEAN HEIGHT**

Average height of a tsunami measured from the trough to the crest after removing the tidal variation.

### **Overflow**

A flowing over; inundation.

### **Post-tsunami survey**

Tsunamis are relatively rare events and most of their evidence is perishable. Therefore, it is very important that reconnaissance surveys be organized and carried out quickly and thoroughly after each tsunami occurs, to collect detailed data valuable for hazard assessment, model validation, and other aspects of tsunami mitigation.



After a major tsunami, physical oceanographers, social scientists, and engineers conduct post-tsunami surveys to collect information. These data, including runup and inundation, deformation, scour, building and structural impact, wave arrival descriptions, and social impact, are important for designing better mitigation to reduce the impacts of tsunami on life and property. Photo courtesy of Philip Liu, Cornell University.

In recent years, following each major destructive tsunami, a post-tsunami reconnaissance survey has been organized to make measurements of runups and inundation limits and to collect associated data from eyewitnesses such as the number of waves, arrival time of waves, and which wave was the largest. The surveys have been organized primarily on an ad-hoc basis by international academic tsunami researchers. A Post-Tsunami Survey Field Guide (http://ioc3.unesco.org/itic/contents.php?id=28) has been prepared by the PTWS to help with preparations of surveys, to identify measurements and observations to be taken. and to standardize data collections. The Tsunami Bulletin Board e-mail service has also been used for quickly organizing international surveys and for sharing of the observations from impacted areas.



Post-tsunami survey measuring runup along a transect inland from the coast. Courtesy of ICMAM, Chennai, DOD, India.

### RECESSION

Drawdown of sea level prior to tsunami flooding. The shoreline moves seaward, sometimes by a kilometre or more, exposing the sea bottom, rocks, and fish. The recession of the sea is a natural warning sign that a tsunami is approaching.



North Shore, Oahu, Hawaii. During the 9 March 1957 Aleutian Island tsunami, people foolishly explored the exposed reef, unaware that tsunami waves would return in minutes to inundate the shoreline. Photo by A. Yamauchi, courtesy of Honolulu Star-Bulletin.

### Rise

The upward change or elevation in sea level associated with a tsunami, a tropical cyclone, storm surge, the tide, or other long term climatic effect.

### RUNUP

1) Difference between the elevation of maximum tsunami penetration (inundation line) and the sea level at the time of the tsunami. In practical terms, runup is only measured where there is a clear evidence of the inundation limit on the shore.

2) Elevation reached by seawater measured relative to some stated datum such as mean sea level, mean low water, sea level at the time of the tsunami attack, etc., and measured ideally at a point that is a local maximum of the horizontal inundation. Where the elevation is not measured at the maximum of horizontal inundation this is often referred to as the inundation-height.

### **RUNUP DISTRIBUTION**

Set of tsunami runup values measured or observed along a coastline.



Tsunami stripped forested hills of vegetation leaving clear marker of tsunami runup, Banda Aceh, 26 December 2004 Sumutra tsunami. Photo courtesy of Yuichi Nishimura, Hokkaido University.



Runup can often be inferred from the vertical extent of dead vegetation, from debris normally found at ground level that are observed stuck on electric wires, in trees, or at other heights, and from water line marks left on building walls. In extreme cases, cars, boats, and other heavy objects have been lifted and deposited atop buildings. Banda Aceh, Indonesia, 26 December 2004. Photo courtesy of C. Courtney, Tetra Tech EMI.

### **SIEBERG TSUNAMI INTENSITY SCALE**

A descriptive tsunami intensity scale, which was later modified into the Sieberg-Ambraseys tsunami intensity scale described below (Ambraseys 1962).

### Modified sieberg sea-wave intensity scale

1) Very light. Wave so weak as to be perceptible only on tide-gauge records.

2) Light. Wave noticed by those living along the shore and familiar with the sea. On very flat shores generally noticed.

3) Rather strong. Generally noticed. Flooding of gently sloping coasts. Light sailing vessels or small boats carried away on shore. Slight damage to light structures situated near the coast. In estuaries reversal of the river flow some distance upstream.

4) Strong. Flooding of the shore to some depth. Light scouring on man-made ground. Embankments and dikes damaged. Light structures near the coasts damaged. Solid structures on the coast injured. Big sailing vessels and small ships carried inland or out to sea. Coasts littered with floating debris.

5) Very strong. General flooding of the shore to some depth. Breakwater walls and solid structures near the sea damaged. Light structures destroyed. Severe scouring of cultivated land and littering of the coast with floating items and sea animals. With the exception of big ships, all other type of vessels carried inland or out to sea. Big bores in estuary rivers. Harbour works damaged. People drowned. Wave accompanied by strong roar.

6) Disastrous. Partial or complete destruction of man-made structures for some distance from the shore. Flooding of coasts to great depths. Big ships severely damaged. Trees uprooted or broken. Many casualties.

### **SIGNIFICANT WAVE HEIGHT**

The average height of the one-third highest waves of a given wave group. Note that the composition of the highest waves depends upon the extent to which the lower waves are considered. In wave record analysis, the average height of the highest one-third of a selected number of waves, this number being determined by dividing the time of record by the significant period. Also called characteristic wave height.

### **S**PREADING

When referring to tsunami waves, it is the spreading of the wave energy over a wider geographical area as the waves propagate away from the source region. The reason for this geographical spreading and reduction of wave energy with distance traveled, is the sphericity of the earth. The tsunami energy will begin converging again at a distance of 90 degrees from the source. Tsunami waves propagating across a large ocean undergo other changes in configuration primarily due to refraction, but geographical spreading is also very important depending upon the orientation, dimensions, and geometry of the tsunami source.

### SUBSIDENCE (UPLIFT)

The permanent movement of land down (subsidence) or up (uplift) due to geologic processes, such as during an earthquake.



The 26 December 2004 earthquake resulted in 1.2 m of land subsidence in the Car Nicobar, Nicobar Islands, India leaving houses that were once above sea level now permanently submerged. Photo courtesy of ICMAM, Chennai, DOD, India.

### **T**SUNAMI AMPLITUDE

Usually measured on a sea level record, it is: 1) the absolute value of the difference between a particular peak or trough of the tsunami and the undisturbed sea level at the time, 2) half the difference between an adjacent peak and trough, corrected for the change of tide between that peak and trough. It is intended to represent the true amplitude of the tsunami wave at some point in the ocean. However, it is often an amplitude modified in some way by the tide gauge response.



Mareogram (sea level) record of a tsunami.



### **TSUNAMI INTENSITY**

Size of a tsunami based on the macroscopic observation of a tsunami's effect on humans, objects including various sizes of marine vessels, and buildings.

The original scale for tsunamis was published by Sieberg (1923), and later modified by Ambraseys (1962) to create a six-category scale. Papadopoulus and Imamura (2001) proposed a new 12-grade intensity scale which is independent of the need to measure physical parameters like wave amplitude, sensitive to the small differences in tsunami effects, and detailed enough for each grade to cover the many possible types of tsunami impact on the human and natural environment. The scale has 12 categories, similar to the Modified Mercalli Intensity Scale used for macroseismic descriptions of earthquake intensity.

### TSUNAMI MAGNITUDE

Size of a tsunami based on the measurement of the tsunami wave on sea level gauges and other instruments.

The scale, originally descriptive and more similar to an intensity, quantifies the size by using measurements of wave height or tsunami runup. lida et al. (1972) described the magnitude (m) as dependent in logarithmic base 2 on the maximum wave height measured in the field, and corresponding to a magnitude range from -1 to 4:

### $m = \log_2 H_{max}$

Hatori (1979) subsequently extended this socalled Imamura-lida scale for far-field tsunamis by including distance in the formulation. Soloviev (1970) suggested that the mean tsunami height may be another good indicator of tsunami size, and the maximum intensity would be that measured nearest to the tsunami source. A variation on this is the Imamura-Soloviev intensity scale I (Soloviev, 1972). Shuto (1993) has suggested the measurement of H as the height where specific types of impact or damage occur, thus proposing a scale which can be used as a predictive quantitative tool for macroscopic effects.

Tsunami magnitudes have also been proposed that are similar in form to those used to calculate

earthquake magnitudes. These include the original formula proposed by Abe (1979) for tsunami magnitude,  $M_{t}$ 

#### $M_t = \log H + B$

where H is the maximum single crest or trough amplitude of the tsunami waves (in meteres) and B is a constant, and the far-field application proposed by Hatori (1986) which adds a distance factor into the calculation.

#### **T**SUNAMI PERIOD

Amount of time that a tsunami wave takes to complete a cycle. Tsunami periods typically range from five minutes to two hours.

### TSUNAMI PERIOD (DOMINANT)

Difference between the arrival time of the highest peak and the next one measured on a water level record.

#### **T**SUNAMI WAVE LENGTH

The horizontal distance between similar points on two successive waves measured perpendicular to the crest. The wave length and the tsunami period give information on the tsunami source. For tsunamis generated by earthquakes, the typical wave length ranges from 20 to 300 km. For tsunamis generated by landslides, the wave length is much shorter, ranging from hundreds of metres to tens of kilometres.

### WATER LEVEL (MAXIMUM)

Difference between the elevation of the highest local water mark and the elevation of the sea level at the time of the tsunami. This is different from maximum runup because the water mark is often not observed at the inundation line, but maybe halfway up the side of a building or on a tree trunk.

### **WAVE CREST**

- 1) The highest part of a wave.
- 2) That part of the wave above still water level.

### **WAVE TROUGH**

20

The lowest part of a wave.



This section contains terms to describe sea level and the instruments used to measure tsunamis.

### **CABLE OCEAN-BOTTOM INSTRUMENT**

An instrument at the ocean bottom connected to the land by a cable that provides power for the measurement and transmission of data from the seafloor to the coast. Cables can extend for tens of kilometers offshore and across oceans. They enable real-time, multi-sensor seafloor observatories to be deployed for long-term monitoring. Examples of sensors on cabled systems are seismometers to measure earthquakes, sensitive pressure gauges to measure tsunamis, geodetic sensors to measure seafloor deformation, and cameras. Japan operates several cable systems.

Sea earth		
Data Colle	oction Center Optical Cable	
		(coast line)
	Tsunamimeter-3	Seismometer-5
Seismometer-4	Seismometer-3	Tsunamimeter-2
S	eismometer-2	Repeater (Signal Enhancer)
	<u>a</u> a	-Augo-
(		

Schematic diagram of cabled ocean system for monitoring earthquakes and tsunamis. Courtesy of JMA.

### COTIDAL

Indicating equality with the tides or a coincidence with the time of high or low tide.

### DEEP-OCEAN ASSESSMENT AND REPORTING OF TSUNAMIS (DART®)

An instrument for the early detection, measurement, and real-time reporting of tsunamis in the open ocean. Developed by the US NOAA Pacific Marine Environmental Laboratory, the DART® system consists of a seafloor bottom pressure recording system capable of detecting tsunamis as small as one cm, and a moored surface buoy for real-time communications. An acoustic link is used to transmit data from the seafloor to the surface buoy. The data are then relayed via a satellite link to ground stations, which demodulate the signals for immediate dissemination to the NOAA tsunami warnings centres. The DART® data, along with state-of-theart numerical modeling technology, are part of a tsunami forecasting system package that will provide site-specific predictions of tsunami impact on the coast.



### Low water

The lowest water level reached during a tide cycle. The accepted popular term is low tide.

### **MAREOGRAM OR MARIGRAM**

1) Record made by a mareograph.

2) Any graphic representation of the rise and fall of the sea level, with time as abscissa and height as ordinate, usually used to measure tides, may also show tsunamis.



#### 17 FEBRUARY 1996 RIAN JAYA TSUNAMI



Mareograms of tsunami signals measured by an underwater gauge located 50 km outside the entrance to Tokyo Bay in about 50 m of water (upper trace), and another gauge located at the shore (lower trace). The tsunami is detected on the outside gauge about 40 minutes before it reaches shore (arrows). The offshore gauge was developed by Japan's Port and Harbours Research Institute.

### MAREOGRAPH

A recording sea level gauge. Also known as a marigraph or tide gauge.

### **MEAN SEA LEVEL**

The average height of the sea surface, based upon hourly observation of tide height on the open coast or in adjacent waters which have free access to the sea. These observations are to have been made over a "considerable" period of time. In the United States, mean sea level is defined as the average height of the surface of the sea for all stages of the tide over a 19-year period. Selected values of mean sea level serve as the sea level datum for all elevation surveys in the United States. Along with mean high water, mean low water, and mean lower low water, mean sea level is a type of tidal datum.

### PROBABLE MAXIMUM WATER LEVEL

A hypothetical water level (exclusive of wave runup from normal wind-generated waves) that might result from the most severe combination of hydrometeorological, geoseismic and other geophysical factors that is considered reasonably possible in the region involved, with each of these factors considered as affecting the locality in a maximum manner. This level represents the physical response of a body of water to maximum applied phenomena such as hurricanes, moving squall lines, other cyclonic meteorological events, tsunamis, and astronomical tide combined with maximum probable ambient hydrological conditions such as wave level with virtually no risk of being exceeded.

### **REFERENCE SEA LEVEL**

The observed elevation differences between geodetic benchmarks are processed through least-squares adjustments to determine orthometric heights referred to a common vertical reference surface, which is the reference sea level. In this way, height values of all benchmarks in the vertical control portion of a surveying agency are made consistent and can be compared directly to determine differences of elevation between benchmarks in a geodetic reference system that may not be directly connected by lines of geodetic leveling. The vertical reference surface in use in the United States, as in most parts of the world, approximates the geoid. The geoid was assumed to be coincident with local mean sea level at 26 tidal stations to obtain the Sea Level Datum of 1929 (SLD 290). National Geodetic Vertical Datum of 1929 (NGVD 29) became a name change only; the same vertical reference system has been in use in the United States since 1929. This important vertical geodetic control system is made possible by a universally accepted, reference sea level.

### **Refraction diagrams**

Models using water depths, direction of wave, separation angle, and ray separation between two adjacent rays as input, produce the path of wave orthogonals, refraction coefficients, wave heights, and travel times.

### SEA LEVEL

The height of the sea at a given time measured relative to some datum, such as mean sea level.

### **SEA LEVEL STATION**

A system consisting of a device such as a tide gauge for measuring the height of sea level, a data collection platform (DCP) for acquiring,



digitizing, and archiving the sea level information digitally, and often a transmission system for delivering the data from the field station to a central data collection centre. The specific requirements of data sampling and data transmission are dependent on the application. The GLOSS programme maintains a core network of sea level stations. For local tsunami monitoring, one-second sampled data streams available in real time are required. For distant tsunamis, warning centres may be able to provide adequate warnings using data acquired in near-real time (one-minute sampled data transmitted every 15 minutes). Sea level stations are also used for sea level rise and climate change studies, where an important requirement is for the very accurate location of the station as acquired through surveying techniques.



Rarotonga sea level station, Avarua Harbor, Cook Islands. The fiberglass electronics package (a), antenna (b), solar panel (c) were installed on a pier. Conduit (d) containing cables connecting the sensor, located at a depth of five feet below low-tide water level, to the data collection platform containing the electronics above, was externally attached to the tube containing the sensor (e).

### **TIDAL WAVE**

1) The wave motion of the tides.

2) Often incorrectly used to describe a tsunami, storm surge, or other unusually high and therefore destructive water levels along a shore that are unrelated to the tides.

### TIDE

The rhythmic, alternate rise and fall of the surface (or water level) of the ocean, and of bodies of water connected with the ocean such as estuaries and gulfs, occurring twice a day over most of the Earth and resulting from the gravitational attraction of the moon (and, in lesser degrees, of the sun) acting unequally on different parts of the rotating Earth.

### **TIDE AMPLITUDE**

One-half of the difference in height between consecutive high water and low water; hence, half of the tidal range.

### **TIDE GAUGE**

A device for measuring the height (rise and fall) of the tide. Especially an instrument for automatically making a continuous graphic record of tide height versus time.

### TIDE STATION

A place where tide observations are obtained.

### **T**SUNAMETER

An instrument for the early detection, measurement, and real-time reporting of tsunamis in the open ocean. Also known as a tsunamimeter. The DART® system and cable deep-ocean pressure sensor are tsunameters.



GLOSS sea level stations employ a number of instruments to measure sea level, including down-looking radars to measure sea level. Port Louis, Mauritius. Photo courtesy of University of Hawaii Sea Level Center.



5 ACRONYMS & ORGANIZATIONS

The IOC Global Tsunami Warning and Mitigation Systems work in partnership with a number of organizations and utilize specific acronyms to describe system governance, and the different tsunami information products.

### **FORECAST POINT**

The location where the Tsunami Warning Centre may provide estimates of tsunami arrival time or wave height.

### GLOSS

Global Sea-Level Observing System. A component of the Global Ocean Observing System (GOOS). The UNESCO IOC established GLOSS in 1985 originally to improve the quality of sea level data as input to studies of long-term sea level change. It consists of a core network of approximately 300 stations distributed along continental coastlines and throughout each of the world's island groups. The GLOSS network also supports sea level monitoring for tsunami warning with minimum operational standards of 15-minute data transmissions of one-minute sampled data.

## GOOS

Global Ocean Observing System. GOOS is a permanent global system for observations, modelling, and analysis of marine and ocean variables to support operational ocean services worldwide. The GOOS Project aims to provide accurate descriptions of the present state of the oceans, including living resources; continuous forecasts of the future conditions of the sea for as far ahead as possible; and the basis for forecasts of climate change. The GOOS Project Office, located at the IOC headquarters in Paris since 1992, provides assistance in the implementation of GOOS.

### GTS

Global Telecommunications System of the World Meteorological Organization (WMO) that directly connects national meteorological and hydrological services worldwide. The GTS is widely used for the near real-time transmission of sea level data for tsunami monitoring. The GTS and other robust communications methods are used for the transmission of tsunami warnings.

### ICG

Intergovernmental Coordination Group. As subsidiary bodies of the UNESCO IOC, the ICG meets to promote, organize, and coordinate regional tsunami mitigation activities, including the issuance of timely tsunami warnings. То achieve this objective requires the participation, cooperation and contribution of many national and international seismic, sea level, communication, and dissemination facilities throughout the region. The ICG is comprised of Member States in the region. Currently, these are ICGs for tsunami warning and mitigation systems in the Pacific, Indian Ocean, Caribbean and adjacent regions, and the north-eastern Atlantic, the Mediterranean and connected seas.

### **ICG/CARIBE-EWS**

Intergovernmental Coordination Group for Tsunami and other Coastal Hazards Warning System for the Caribbean and Adjacent Regions established by Resolution XXIII-14 of the 23rd Session of the IOC General Assembly in 2005. The ICG is comprised principally of IOC Member States and regional organizations from the Wider Caribbean Region. Through the coordinating efforts of the IOCARIBE Sub-commission starting in 1993, a Group of Experts formulated a proposal for the building of the Intra-Americas Tsunami Warning System that was endorsed by the IOC General Assembly in 2002.

(http://ioc3.unesco.org/cartws)



### ICG/IOTWS

Intergovernmental Coordination Group for the Indian Ocean Tsunami Warning and Mitigation System established by Resolution XXIII-12 of the 23rd Session of the IOC General Assembly in 2005. The IOC Regional Programme Office in Perth, Australia, serves as the IOTWS Secretariat. Presently, there are 27 Member States. (http://ioc.unesco.org/indotsunami)

### ICG/ITSU

International Coordination Group for the International Tsunami Warning System in the Pacific established by Resolution IV-6 of the 4th Session of the IOC General Assembly in 1965. The ICG/ITSU was renamed to the ICG/PTWS in 2005.

### **ICG/NEAMTWS**

Intergovernmental Coordination Group for the Tsunami Early Warning and Mitigation System in the North-eastern Atlantic, the Mediterranean and Connected Seas established by Resolution XXIII-13 of the 23rd Session of the IOC General Assembly in 2005. The ICG is comprised principally of IOC Member States bordering the north-eastern Atlantic and those bordering or within the Mediterranean or connected seas. (http://ioc3.unesco.org/neamtws)

### **ICG/PTWS**

Intergovernmental Coordination Group for the Pacific Tsunami Warning and Mitigation System, renamed by Resolution ITSU-XX.1 of the 20th Session of the ICG/ITSU in 2005. Presently, there are 32 Member States. The ICG/PTWS was formerly the ICG/ITSU. (http://ioc3.unesco.org/ptws)

### ICG TSUNAMI NATIONAL CONTACT (TNC)

The person designated by an ICG Member State government to represent his/her country in the coordination of international tsunami warning and mitigation activities. The person is part of the main stakeholders of the national tsunami warning and mitigation system programme. The person may



be the Tsunami Warning Focal Point, from the national disaster management organization, from a technical or scientific institution, or from another agency with tsunami warning and mitigation responsibilities.

# ICG TSUNAMI WARNING FOCAL

### POINT (TWFP)

The 7x24 contact person, or other official point of contact or address, for rapidly receiving and issuing tsunami event information (such as warnings). The Tsunami Warning Focal Point either is the emergency authority (civil defense or other designated agency responsible for public safety), or has the responsibility of notifying the emergency authority of the event characteristics (earthquake and/or tsunami), in accordance with national standard operating procedures. The Tsunami Warning Focal Point receives international tsunami warnings from the PTWC, WC/ATWC, the JMA NWPTAC, or other regional warning centres.

### IOC

Intergovernmental Oceanographic Commission of UNESCO. The IOC provides Member States of the United Nations with an essential mechanism for global cooperation in the study of the ocean. The IOC assists governments to address their individual and collective ocean and coastal problems through the sharing of knowledge, information, and technology, and through the coordination of national programmes. (http://ioc-unesco.org/)

### ITIC

International Tsunami Information Centre. ITIC was established in November 1965 by the IOC of UNESCO to support the ICG/ITSU in the Pacific. The ITIC also provides technical and capacity building assistance to Member States for the global establishment of tsunami warning and mitigation systems in the Indian and Atlantic Oceans, the Caribbean and Mediterranean Seas, and other oceans and marginal seas. In the Pacific, the ITIC specifically monitors and recommends improvements to the PTWS, coordinates tsunami technology transfer among Member States interested in establishing regional and national tsunami warning systems, acts as a clearinghouse for risk assessment and mitigation activities, and serves as a resource for the development, publication, and distribution of tsunami education and preparedness materials. (http://www.tsunamiwave.info)

### IUGG

International Union of Geodesy and Geophysics. The IUGG is a non-governmental, scientific organization established in 1919, dedicated to promoting and coordinating studies of the Earth and its environment in space. The IUGG Tsunami Commission, established in 1960, is an international group of scientists concerned with various aspects of tsunamis, including an improved understanding of the dynamics of generation, propagation, and coastal runup of tsunamis, as well as their consequences to society. (http://iugg.org)

### JMA

Japan Meteorological Agency. JMA established a tsunami warning service in 1952. JMA now serves as a National Tsunami Warning System that continuously monitors 24 hours-a-day all seismic activity in Japan, and issues timely information concerning earthquakes and tsunamis. In 2005, the JMA began operations of the Northwest Pacific Tsunami Advisory Center (NWPTAC). The NWPTAC provides supplementary tsunami information for events in and around Japan and the northwest Pacific, and interim services for the South China Sea region, in close coordination with the PTWC. Since 2005, JMA and PTWC have provided interim services for the Indian Ocean. (http://www.jma.go.jp/jma)

### **MASTER PLAN**

The principal long-term guide for improving the TWS. The Plan provides a summary of the basic elements which comprise the TWS, a description of its existing components, and an outline of the activities, data sets, methods, and procedures that need to be improved in order to reduce tsunami risk. The first edition of the ICG/PTWS Master Plan was released in 1989. The second edition was released in 1999.

(http://ioc3.unesco.org/itic/categories.php?categ ory\_no=64)

### **O**CEAN-WIDE TSUNAMI WARNING

A warning issued to all participants after there is confirmation of tsunami waves capable of causing destruction beyond the local area. Ocean-Wide Tsunami Warnings contain estimated tsunami arrival times (ETAs) at all Forecast Points. Ocean-Wide Tsunami Warning Bulletins also normally carry information on selected wave heights and other wave reports. The Warning will be cancelled when it is determined that the tsunami threat is over. As local conditions can cause wide variations in tsunami wave action, the all-clear determination should be made by the local action agencies and not the TWC. In general, after receipt of a Tsunami Warning, action agencies can assume all-clear status when their area is free from damaging waves for at least two hours, unless additional ETAs have been announced by the TWC (for example for a significant aftershock) or local conditions, that may include continued seiching or particularly strong currents in channels and harbours, warrant the continuation of the Tsunami Warning status.

#### SAMPLE: Pacific-Wide Tsunami Warning (initial)

TSUNAMI BULLETIN NUMBER 004 PACIFIC TSUNAMI WARNING CENTER/NOAA/NWS ISSUED AT 1050Z 10 JUL 2008

THIS BULLETIN APPLIES TO AREAS WITHIN AND BORDERING THE PACIFIC OCEAN AND ADJACENT SEAS...EXCEPT ALASKA...BRITISH COLUMBIA... WASHINGTON...OREGON AND CALIFORNIA.

... A WIDESPREAD TSUNAMI WARNING IS IN EFFECT ...

A TSUNAMI WARNING IS IN EFFECT FOR

CHILE / PERU / ECUADOR / COLOMBIA / ANTARCTICA / PANAMA / COSTA RICA / PITCAIRN / NICARAGUA / HONDURAS / FR. POLYNESIA / EL SALVADOR / GUATEMALA / MEXICO / COOK ISLANDS / KIRIBATI / KERMADEC IS / NIUE / NEW ZEALAND / TONGA / AMERICAN SAMOA / SAMOA / JARVIS IS. / WALLIS-FUTUNA / TOKELAU / FIJI / AUSTRALIA / HAWAII / PALMYRA IS. / TUVALU / VANUATU / HOWLAND-BAKER / NEW CALEDONIA / JOHNSTON IS. / SOLOMON IS. / NAURU / MARSHALL IS. / MIDWAY IS. / KOSRAE / PAPUA NEW GUINEA / POHNPEI / WAKE IS. / CHUUK / RUSSIA / MARCUS IS. / N. MARIANAS / INDONESIA / GUAM / YAP / BELAU / JAPAN / PHILIPPINES / CHINESE TAIPEI / TAIWAN

THIS BULLETIN IS ISSUED AS ADVICE TO GOVERNMENT AGENCIES. ONLY NATIONAL AND LOCAL GOVERNMENT AGENCIES HAVE THE AUTHORITY TO MAKE DECISIONS REGARDING THE OFFICIAL STATE OF ALERT IN THEIR AREA AND ANY ACTIONS TO BE TAKEN IN RESPONSE.

AN EARTHQUAKE HAS OCCURRED WITH THESE PRELIMINARY PARAMETERS

ORIGIN TIME - 0809Z 10 JUL 2008 COORDINATES - 35.2 SOUTH 75.1 WEST DEPTH - 40 KM LOCATION - OFF COAST OF CENTRAL CHILE MAGNITUDE - 8.9 MEASUREMENTS OR REPORTS OF TSUNAMI WAVE ACTIVITY

GAUGE LOCATION	LAT	LON	TIME	AMPL	PER
JUAN FERNANDEZ VALPARAISO CL SAN ANTONIO CL TALCAHUANO CL	33.0S 33.6S	71.6W 71.6W	1011Z 0948Z	2.33M / 1.1FT 1.53M / 1.7FT 1.52M / 1.7FT 1.95M / 3.1FT	29MIN 33MIN

LAT - LATITUDE (N-NORTH, S-SOUTH)

LON - LONGITUDE (E-EAST, W-WEST)

- TIME TIME OF THE MEASUREMENT (Z IS UTC IS GREENWICH TIME)
- AMPL TSUNAMI AMPLITUDE MEASURED RELATIVE TO NORMAL SEA LEVEL.

IT IS ...NOT... CREST-TO-TROUGH WAVE HEIGHT. VALUES ARE GIVEN IN BOTH METERS(M) AND FEET(FT).

PER - PERIOD OF TIME IN MINUTES(MIN) FROM ONE WAVE TO THE NEXT.

#### **EVALUATION**

SEA LEVEL READINGS CONFIRM THAT A TSUNAMI HAS BEEN GENERATED WHICH COULD CAUSE WIDESPREAD DAMAGE. AUTHORITIES SHOULD TAKE APPROPRIATE ACTION IN RESPONSE TO THIS THREAT. THIS CENTER WILL CONTINUE TO MONITOR SEA LEVEL DATA TO DETERMINE THE EXTENT AND SEVERITY OF THE THREAT.

A TSUNAMI IS A SERIES OF WAVES AND THE FIRST WAVE MAY NOT BE THE LARGEST. TSUNAMI WAVE HEIGHTS CANNOT BE PREDICTED AND CAN VARY SIGNIFICANTLY ALONG A COAST DUE TO LOCAL EFFECTS. THE TIME FROM ONE TSUNAMI WAVE TO THE NEXT CAN BE FIVE MINUTES TO AN HOUR, AND THE THREAT CAN CONTINUE FOR MANY HOURS AS MULTIPLE WAVES ARRIVE.

FOR ALL AREAS - WHEN NO MAJOR WAVES ARE OBSERVED FOR TWO HOURS AFTER THE ESTIMATED TIME OF ARRIVAL OR DAMAGING WAVES HAVE NOT OCCURRED FOR AT LEAST TWO HOURS THEN LOCAL AUTHORITIES CAN ASSUME THE THREAT IS PASSED. DANGER TO BOATS AND COASTAL STRUCTURES CAN CONTINUE FOR SEVERAL HOURS DUE TO RAPID CURRENTS. AS LOCAL CONDITIONS CAN CAUSE A WIDE VARIATION IN TSUNAMI WAVE ACTION THE ALL CLEAR DETERMINATION MUST BE MADE BY LOCAL AUTHORITIES.

ESTIMATED INITIAL TSUNAMI WAVE ARRIVAL TIMES AT FORECAST POINTS WITHIN THE WARNING AND WATCH AREAS ARE GIVEN BELOW. ACTUAL ARRIVAL TIMES MAY DIFFER AND THE INITIAL WAVE MAY NOT BE THE LARGEST. A TSUNAMI IS A SERIES OF WAVES AND THE TIME BETWEEN SUCCESSIVE WAVES CAN BE FIVE MINUTES TO ONE HOUR.

LOCATION	FORECAST POINT	COORDINATES	ARRIVAL TIME
CHILE	VALPARAISO TALCAHUANO COQUIMBO CORRAL CALDERA ANTOFAGASTA IQUIQUE ARICA GOLFO DE PENAS PUERTO MONTT EASTER IS. PUNTA ARENAS PUERTO WILLIAMS	33.0S 71.6W 36.7S 73.1W 29.9S 71.3W 39.8S 73.5W 27.1S 70.8W 23.3S 70.4W 20.2S 70.1W 18.5S 70.3W 47.1S 74.9W 41.5S 73.0W 27.1S 109.4W 53.2S 70.9W 54.8S 68.2W	0550Z 10 JUL 0603Z 10 JUL 0610Z 10 JUL 0621Z 10 JUL 0631Z 10 JUL 0654Z 10 JUL 0721Z 10 JUL 0738Z 10 JUL 0745Z 10 JUL 1001Z 10 JUL 1024Z 10 JUL 1215Z 10 JUL

\* NOTE: ALL STATIONS ARE NOT LISTED IN THIS SAMPLE

BULLETINS WILL BE ISSUED HOURLY OR SOONER IF CONDITIONS WARRANT. THE TSUNAMI WARNING WILL REMAIN IN EFFECT UNTIL FURTHER NOTICE.

THE WEST COAST/ALASKA TSUNAMI WARNING CENTER WILL ISSUE PRODUCTS FOR ALASKA...BRITISH COLUMBIA...WASHINGTON...OREGON...CALIFORNIA.

### **OPERATIONAL USERS GUIDE FOR THE** TSUNAMI WARNING SYSTEM

The Guide includes a summary of the administrative and operational services and procedures, including monitoring and detection data networks that are used by the warning centres, the criteria for the reporting and issuing of tsunami information messages, samples messages, the recipients of the information, and the methods by which the messages are sent. Background information to assist customers in understanding the products that are issued may also be included. Formerly called the Communications Plan for the TWS.



PTWC facilities located at Ewa Beach, Hawaii, USA.



PTWC operations area.

### **PTWC AND WC/ATWC**

Established in 1949, the Richard H. Hagemeyer Pacific Tsunami Warning Center (PTWC) in Ewa Beach, Hawaii, serves as the warning operations headquarters for the PTWS and works closely with sub-regional and national centres in monitoring and evaluating potentially tsunamigenic earthquakes. It provides international warning advisories for teletsunamis to countries in the Pacific, and warnings for



Hawaii and US Pacific island interests. PTWC has provided interim services for the Indian Ocean and the wider Caribbean since 2005. Established in 1964, the West Coast and Alaska Tsunami Warning Center (WC/ATWC) provides warning services to the continental USA, Puerto Rico, the Virgin Islands, and Canada, and serves as a back up to PTWC.

(http://www.prh.noaa.gov/ptwc) (http://wcatwc.arh.noaa.gov/)



Global seismic network used by PTWC (March 2008).



Global sea level network used by PTWC (July 2008).

### **REGIONAL EXPANDING TSUNAMI** WATCH/WARNING BULLETIN (RWW)

A PTWC PTWS message issued initially using only seismic information to alert countries of the possibility of a tsunami and advise that a tsunami investigation is underway. In the Pacific, Tsunami Warning status will encompass regions having less than three hours until the estimated time of tsunami arrival. Those areas having three to six hours will be placed in a Watch status. Additional bulletins will be issued hourly or sooner until either a Pacific-wide tsunami is confirmed or no further tsunami threat exists.

# SAMPLE: Expanding Regional Tsunami Warning and Watch (initial)

TSUNAMI BULLETIN NUMBER 001 PACIFIC TSUNAMI WARNING CENTER/NOAA/NWS ISSUED AT 0821Z 10 JUL 2008

THIS BULLETIN APPLIES TO AREAS WITHIN AND BORDERING THE PACIFIC OCEAN AND ADJACENT SEAS...EXCEPT ALASKA...BRITISH COLUMBIA... WASHINGTON...OREGON AND CALIFORNIA.

... A TSUNAMI WARNING AND WATCH ARE IN EFFECT ...

A TSUNAMI WARNING IS IN EFFECT FOR

CHILE / PERU

A TSUNAMI WATCH IS IN EFFECT FOR

ECUADOR / COLOMBIA

FOR ALL OTHER AREAS COVERED BY THIS BULLETIN... IT IS FOR INFORMATION ONLY AT THIS TIME.

THIS BULLETIN IS ISSUED AS ADVICE TO GOVERNMENT AGENCIES. ONLY NATIONAL AND LOCAL GOVERNMENT AGENCIES HAVE THE AUTHORITY TO MAKE DECISIONS REGARDING THE OFFICIAL STATE OF ALERT IN THEIR AREA AND ANY ACTIONS TO BE TAKEN IN RESPONSE.

AN EARTHQUAKE HAS OCCURRED WITH THESE PRELIMINARY PARAMETERS

ORIGIN TIME - 0809Z 10 JUL 2008 COORDINATES - 35.2 SOUTH 75.1 WEST DEPTH - 40 KM LOCATION - OFF COAST OF CENTRAL CHILE MAGNITUDE - 8.2

#### EVALUATION

IT IS NOT KNOWN THAT A TSUNAMI WAS GENERATED. THIS WARNING IS BASED ONLY ON THE EARTHQUAKE EVALUATION. AN EARTHQUAKE OF THIS SIZE HAS THE POTENTIAL TO GENERATE A DESTRUCTIVE TSUNAMI THAT CAN STRIKE COASTLINES NEAR THE EPICENTER WITHIN MINUTES AND MORE DISTANT COASTLINES WITHIN HOURS. AUTHORITIES SHOULD TAKE APPROPRIATE ACTION IN RESPONSE TO THIS POSSIBILITY. THIS CENTER WILL MONITOR SEA LEVEL DATA FROM GAUGES NEAR THE EARTHQUAKE TO DETERMINE IF A TSUNAMI WAS GENERATED AND ESTIMATE THE SEVERITY OF THE THREAT. ESTIMATED INITIAL TSUNAMI WAVE ARRIVAL TIMES AT FORECAST POINTS WITHIN THE WARNING AND WATCH AREAS ARE GIVEN BELOW. ACTUAL ARRIVAL TIMES MAY DIFFER AND THE INITIAL WAVE MAY NOT BE THE LARGEST. A TSUNAMI IS A SERIES OF WAVES AND THE TIME BETWEEN SUCCESSIVE WAVES CAN BE FIVE MINUTES TO ONE HOUR.

LOCATION	FORECAST POINT	COORDINATES	ARRIVAL TIME
-			
CHILE	VALPARAISO	33.0S 71.6W	0850Z 10 JUL
	TALCAHUANO COQUIMBO	36.7S 73.1W 29.9S 71.3W	0903Z 10 JUL 0910Z 10 JUL
	CORRAI	39.8S 73.5W	0921Z 10 JUL
	CALDERA	27.1S 70.8W	0931Z 10 JUL
	ANTOFAGASTA	23.3S 70.4W	0954Z 10 JUL
	IQUIQUE	20.2S 70.1W	1021Z 10 JUL
	ARICA	18.5S 70.3W	1038Z 10 JUL
	GOLFO DE PENAS	47.1S 74.9W	1045Z 10 JUL
	PUERTO MONTT	41.5S 73.0W	1203Z 10 JUL
	EASTER IS. PUNTA ARENAS	27.1S 109.4W 53.2S 70.9W	1301Z 10 JUL 1324Z 10 JUL
PERU	MOLLENDO	17.1S 72.0W	1045Z 10 JUL
I LINO	SAN JUAN	15.3S 75.2W	11027 10 JUI
	LA PUNTA	12.1S 77.2W	1155Z 10 JUL
	PIMENTAL	6.9S 80.0W	1223Z 10 JUL
	TALARA	4.6S 81.5W	1236Z 10 JUL
	CHIMBOTE	9.0S 78.8W	1242Z 10 JUL
ECUADOR		2.2S 81.2W	1312Z 10 JUL
	ESMERELDAS BALTRA IS.	1.2N 79.8W 0.5S 90.3W	1343Z 10 JUL 1415Z 10 JUL
COLOMBIA		0.55 90.3W 1.8N 78.9W	14152 10 JUL 14027 10 JUI
OOLOWDIA	IOMAGO	1.011 70.300	14022 10 JOL



BULLETINS WILL BE ISSUED HOURLY OR SOONER IF CONDITIONS WARRANT. THE TSUNAMI WARNING AND WATCH WILL REMAIN IN EFFECT UNTIL FURTHER NOTICE.

THE WEST COAST/ALASKA TSUNAMI WARNING CENTER WILL ISSUE PRODUCTS FOR ALASKA... BRITISH COLUMBIA...WASHINGTON...OREGON... CALIFORNIA.

## SAMPLE: Expanding Regional Tsunami Warning and Watch (cancellation)

TSUNAMI BULLETIN NUMBER 004 PACIFIC TSUNAMI WARNING CENTER/NOAA/NWS ISSUED AT 1052Z 10 JUL 2008

THIS BULLETIN APPLIES TO AREAS WITHIN AND BORDERING THE PACIFIC OCEAN AND ADJACENT SEAS...EXCEPT ALASKA...BRITISH COLUMBIA... WASHINGTON...OREGON AND CALIFORNIA.

... TSUNAMI WARNING CANCELLATION ...

THE TSUNAMI WARNING AND/OR WATCH ISSUED BY THE PACIFIC TSUNAMI WARNING CENTER IS NOW CANCELLED FOR

CHILE / PERU / ECUADOR / COLOMBIA / ANTARCTICA / PANAMA / COSTA RICA / PITCAIRN / NICARAGUA / HONDURAS / FR. POLYNESIA / EL SALVADOR / GUATEMALA / MEXICO

THIS BULLETIN IS ISSUED AS ADVICE TO GOVERNMENT AGENCIES. ONLY NATIONAL AND LOCAL GOVERNMENT AGENCIES HAVE THE AUTHORITY TO MAKE DECISIONS REGARDING THE OFFICIAL STATE OF ALERT IN THEIR AREA AND ANY ACTIONS TO BE TAKEN IN RESPONSE.

AN EARTHQUAKE HAS OCCURRED WITH THESE PRELIMINARY PARAMETERS

ORIGIN TIME - 0809Z 10 JUL 2008 COORDINATES - 35.2 SOUTH 75.1 WEST DEPTH - 40 KM LOCATION - OFF COAST OF CENTRAL CHILE MAGNITUDE - 8.3

MEASUREMENTS OR REPORTS OF TSUNAMI WAVE ACTIVITY

GAUGE LOCATION	LAT LON	TIME	AMPL	PER
JUAN FERNANDEZ	33.6S 78.8W	1040Z	0.33M / 1.1FT	23MIN
VALPARAISO CL	33.0S 71.6W	1011Z	0.53M / 1.7FT	19MIN
SAN ANTONIO CL	33.6S 71.6W	0948Z	0.52M / 1.7FT	18MIN
TALCAHUANO CL	36.7S 73.1W	0923Z	0.95M / 3.1FT	22MIN

LAT - LATITUDE (N-NORTH, S-SOUTH)

LON - LONGITUDE (E-EAST, W-WEST)

TIME - TIME OF THE MEASUREMENT (Z IS UTC IS GREENWICH TIME)

AMPL - TSUNAMI AMPLITUDE MEASURED RELATIVE TO NORMAL SEA LEVEL. IT IS ...NOT... CREST-TO-TROUGH WAVE HEIGHT. VALUES ARE GIVEN IN BOTH METERS(M) AND

VALUES ARE GIVEN IN BOTH METERS(M) AND FEET(FT). PER - PERIOD OF TIME IN MINUTES(MIN) FROM ONE

WAVE TO THE NEXT.

#### EVALUATION

SEA LEVEL READINGS INDICATE A TSUNAMI WAS GENERATED. IT MAY HAVE BEEN DESTRUCTIVE ALONG COASTS NEAR THE EARTHQUAKE EPICENTER. FOR THOSE AREAS - WHEN NO MAJOR WAVES ARE OBSERVED FOR TWO HOURS AFTER THE ESTIMATED TIME OF ARRIVAL OR DAMAGING WAVES HAVE NOT OCCURRED FOR AT LEAST TWO HOURS THEN LOCAL AUTHORITIES CAN ASSUME THE THREAT IS PASSED. DANGER TO BOATS AND COASTAL STRUCTURES CAN CONTINUE FOR SEVERAL HOURS DUE TO RAPID CURRENTS. AS LOCAL CONDITIONS CAN CAUSE A WIDE VARIATION IN TSUNAMI WAVE ACTION THE ALL CLEAR DETERMINATION MUST BE MADE BY LOCAL AUTHORITIES.

NO TSUNAMI THREAT EXISTS FOR OTHER COASTAL AREAS IN THE PACIFIC ALTHOUGH SOME OTHER AREAS MAY EXPERIENCE SMALL SEA LEVEL CHANGES. -THE TSUNAMI WARNING IS NOW CANCELLED FOR ALL AREAS COVERED BY THIS CENTER.

THIS WILL BE THE FINAL BULLETIN ISSUED FOR THIS EVENT UNLESS ADDITIONAL INFORMATION BECOMES AVAILABLE.

THE WEST COAST/ALASKA TSUNAMI WARNING CENTER WILL ISSUE PRODUCTS FOR ALASKA...BRITISH COLUMBIA...WASHINGTON...OREGON...CALIFORNIA.

### **R**EGIONAL FIXED TSUNAMI WARNING BULLETIN

A PTWC PTWS message issued initially using only seismic information to alert all participants of the possibility of a tsunami and advise that a tsunami investigation is underway. The area placed in a Tsunami Warning status encompasses coastal regions within 1,000 km of the earthquake epicentre. A Regional Fixed Tsunami Warning will be followed by additional bulletins without expanding the warning area until it is either upgraded or is cancelled.

# SAMPLE: Fixed Regional Tsunami Warning (initial)

TSUNAMI BULLETIN NUMBER 001 PACIFIC TSUNAMI WARNING CENTER/NOAA/NWS ISSUED AT 1556Z 14 NOV 2007

THIS BULLETIN APPLIES TO AREAS WITHIN AND BORDERING THE PACIFIC OCEAN AND ADJACENT SEAS...EXCEPTALASKA...BRITISH COLUMBIA... WASHINGTON...OREGON AND CALIFORNIA.

... A TSUNAMI WARNING IS IN EFFECT ...

ATSUNAMI WARNING IS IN EFFECT FOR

CHILE/PERU

FOR ALL OTHER AREAS COVERED BY THIS BULLETIN... IT IS FOR INFORMATION ONLY AT THIS TIME.

THIS BULLETIN IS ISSUED AS ADVICE TO GOVERNMENT AGENCIES. ONLY NATIONAL AND LOCAL GOVERNMENT AGENCIES HAVE THE AUTHORITY TO MAKE DECISIONS REGARDING THE OFFICIAL STATE OF ALERT IN THEIR AREA AND ANY ACTIONS TO BE TAKEN IN RESPONSE.

AN EARTHQUAKE HAS OCCURRED WITH THESE PRELIMINARY PARAMETERS

ORIGIN TIME - 1541Z 14 NOV 2007 COORDINATES - 22.2 SOUTH 69.9 WEST DEPTH - 59 KM LOCATION - NORTHERN CHILE MAGNITUDE - 7.7

#### **EVALUATION**

IT IS NOT KNOWN THAT A TSUNAMI WAS GENERATED. THIS WARNING IS BASED ONLY ON THE EARTHQUAKE EVALUATION. AN EARTHQUAKE OF THIS SIZE HAS THE POTENTIAL TO GENERATE A DESTRUCTIVE TSUNAMI THAT CAN STRIKE COASTLINES IN THE REGION NEAR THE



EPICENTER WITHIN MINUTES TO HOURS. AUTHORITIES IN THE REGION SHOULD TAKE APPROPRIATE ACTION IN RESPONSE TO THIS POSSIBILITY. THIS CENTER WILL MONITOR SEA LEVEL GAUGES NEAREST THE REGION AND REPORT IF ANY TSUNAMI WAVE ACTIVITY IS OBSERVED. THE WARNING WILL NOT EXPAND TO OTHER AREAS OF THE PACIFIC UNLESS ADDITIONAL DATA ARE RECEIVED TO WARRANT SUCH AN EXPANSION.

ESTIMATED INITIAL TSUNAMI WAVE ARRIVAL TIMES AT FORECAST POINTS WITHIN THE WARNING AND WATCH AREAS ARE GIVEN BELOW. ACTUAL ARRIVAL TIMES MAY DIFFER AND THE INITIAL WAVE MAY NOT BE THE LARGEST. ATSUNAMI IS A SERIES OF WAVES AND THE TIME BETWEEN SUCCESSIVE WAVES CAN BE FIVE MINUTES TO ONE HOUR.

LOCATIO	N FORECAST POINT	COORDINATES	ARRIVAL TIME
CHILE	ANTOFAGASTA	23.3S 70.4W	1612Z 14 NOV
	IQUIQUE	20.2S 70.1W	1625Z 14 NOV
	CALDERA	27.1S 70.8W	1642Z 14 NOV
	ARICA	18.5S 70.3W	1643Z 14 NOV
	COQUIMBO	29.9S 71.3W	1704Z 14 NOV
PERU	MOLLENDO	17.1S 72.0W	1650Z 14 NOV
	SAN JUAN	15.3S 75.2W	1706Z 14 NOV

BULLETINS WILL BE ISSUED HOURLY OR SOONER IF CONDITIONS WARRANT. THE TSUNAMI WARNING WILL REMAIN IN EFFECT UNTIL FURTHER NOTICE.

THE WEST COAST/ALASKA TSUNAMI WARNING CENTER WILL ISSUE PRODUCTS FOR ALASKA...BRITISH COLUMBIA...WASHINGTON...OREGON...CALIFORNIA.

# SAMPLE: Fixed Regional Tsunami Warning (cancellation)

TSUNAMI BULLETIN NUMBER 002 PACIFIC TSUNAMI WARNING CENTER/NOAA/NWS ISSUED AT 1656Z 14 NOV 2007

THIS BULLETIN APPLIES TO AREAS WITHIN AND BORDERING THE PACIFIC OCEAN AND ADJACENT SEAS...EXCEPT ALASKA...BRITISH COLUMBIA... WASHINGTON...OREGON AND CALIFORNIA.

... TSUNAMI WARNING CANCELLATION ...

THE TSUNAMI WARNING AND/OR WATCH ISSUED BY THE PACIFIC TSUNAMI WARNING CENTER IS NOW CANCELLED FOR

#### CHILE / PERU

THIS BULLETIN IS ISSUED AS ADVICE TO GOVERNMENT AGENCIES. ONLY NATIONAL AND LOCAL GOVERNMENT AGENCIES HAVE THE AUTHORITY TO MAKE DECISIONS REGARDING THE OFFICIAL STATE OF ALERT IN THEIR AREA AND ANY ACTIONS TO BE TAKEN IN RESPONSE.

AN EARTHQUAKE HAS OCCURRED WITH THESE PRELIMINARY PARAMETERS

ORIGIN TIME - 1541Z 14 NOV 2007 COORDINATES - 22.2 SOUTH 69.9 WEST DEPTH - 59 KM LOCATION - NORTHERN CHILE MAGNITUDE - 7.7

MEASUREMENTS OR REPORTS OF TSUNAMI WAVE ACTIVITY

GAUGE LOCATION	LAT	LON	TIME	AMPL	PER
ANTOFAGASTA CL	23.6S	70.4W	1614Z	0.07M/ 0.2FT	20MIN

LAT - LATITUDE (N-NORTH, S-SOUTH)

- LON LONGITUDE (E-EAST, W-WEST)
- TIME TIME OF THE MEASUREMENT (Z IS UTC IS GREENWICH TIME)
- AMPL TSUNAMI AMPLITUDE MEASURED RELATIVE TO NORMAL SEA LEVEL. IT IS ...NOT... CREST-TO-TROUGH WAVE HEIGHT. VALUES ARE GIVEN IN BOTH METERS(M) AND FEET(FT).
- PER PERIOD OF TIME IN MINUTES(MIN) FROM ONE WAVE TO THE NEXT.

#### **EVALUATION**

SEA LEVEL READINGS INDICATE A TSUNAMI WAS GENERATED. IT MAY HAVE BEEN DESTRUCTIVE ALONG COASTS NEAR THE EARTHQUAKE EPICENTER. FOR THOSE AREAS - WHEN NO MAJOR WAVES ARE OBSERVED FOR TWO HOURS AFTER THE ESTIMATED TIME OF ARRIVAL OR DAMAGING WAVES HAVE NOT OCCURRED FOR AT LEAST TWO HOURS THEN LOCAL AUTHORITIES CAN ASSUME THE THREAT IS PASSED. DANGER TO BOATS AND COASTAL STRUCTURES CAN CONTINUE FOR SEVERAL HOURS DUE TO RAPID CURRENTS. AS LOCAL CONDITIONS CAN CAUSE A WIDE VARIATION IN TSUNAMI WAVE ACTION THE ALL CLEAR DETERMINATION MUST BE MADE BY LOCAL AUTHORITIES.

PTWC HAS RECEIVED A REPORT FROM CHILE THAT NO SIGNIFICANT TSUNAMI WAVE ACTIVITY HAS BEEN OBSERVED.

NO TSUNAMI THREAT EXISTS FOR OTHER COASTAL AREAS IN THE PACIFIC ALTHOUGH SOME OTHER AREAS MAY EXPERIENCE SMALL SEA LEVEL CHANGES. THE TSUNAMI WARNING IS NOW CANCELLED FOR ALL AREAS COVERED BY THIS CENTER.

THIS WILL BE THE FINAL BULLETIN ISSUED FOR THIS EVENT UNLESS ADDITIONAL INFORMATION BECOMES AVAILABLE.

THE WEST COAST/ALASKA TSUNAMI WARNING CENTER WILL ISSUE PRODUCTS FOR ALASKA...BRITISH COLUMBIA...WASHINGTON... OREGON...CALIFORNIA.

#### TSUNAMI BULLETIN BOARD (TBB)

TBB is an ITIC-sponsored e-mail service that provides an open, objective scientific forum for the posting and discussion of news and information relating to tsunamis and tsunami research. The ITIC provides the service to tsunami researchers and other technical professionals for the purpose of facilitating the widespread dissemination of information on tsunami events, current research investigations, and announcements for upcoming meetings, publications, and other tsunami-related materials. All members of the TBB are welcome to contribute. Messages are immediately broadcast without modification. The TBB has been very useful for helping to rapidly organize posttsunami surveys, for distributing their results, and for planning tsunami workshops and symposia. Members of the TBB automatically receive the tsunami bulletins issued by the PTWC, WC/ATWC, and JMA.



### **TSUNAMI EMERGENCY RESPONSE (TER)**

Tsunami Emergency Response (TER) describes the actions taken to ensure public safety by responsible agencies after notification by the Tsunami Warning Focal Point (TWFP), typically the national Tsunami Warning Centre. It includes Standard Operating Procedures and Protocols for emergency response and action, organizations and individuals involved and their roles and responsibilities, contact information, timeline and urgency assigned to action, and means by which both ordinary citizens and special needs populations (physically or mentally handicapped, elderly, transient, and marine populations) will be alerted. For tsunami response, emphasis is placed on the rapidness, efficiency, conciseness, and clarity of the actions and instructions to the public. A Tsunami Emergency Response Plan should also include post-tsunami actions and responsibilities for search and rescue, relief, rehabilitation, and recovery.

### **TSUNAMI INFORMATION BULLETIN (TIB)**

TWC message product advising the occurrence of a major earthquake with an evaluation that there is either: a) no widespread tsunami threat but the small possibility of a local tsunami or b) there is no tsunami threat at all that indicates there is no tsunami threat.

#### SAMPLE: Tsunami Information Bulletin

TSUNAMI BULLETIN NUMBER 001 PACIFIC TSUNAMI WARNING CENTER/NOAA/NWS ISSUED AT 0222Z 05 JUL 2008

THIS BULLETIN APPLIES TO AREAS WITHIN AND BORDERING THE PACIFIC OCEAN AND ADJACENT SEAS...EXCEPT ALASKA...BRITISH COLUMBIA... WASHINGTON...OREGON AND CALIFORNIA.

... TSUNAMI INFORMATION BULLETIN ...

THIS BULLETIN IS FOR INFORMATION ONLY.

THIS BULLETIN IS ISSUED AS ADVICE TO GOVERNMENT AGENCIES. ONLY NATIONAL AND LOCAL GOVERNMENT AGENCIES HAVE THE AUTHORITY TO MAKE DECISIONS REGARDING THE OFFICIAL STATE OF ALERT IN THEIR AREA AND ANY ACTIONS TO BE TAKEN IN RESPONSE.

AN EARTHQUAKE HAS OCCURRED WITH THESE PRELIMINARY PARAMETERS

ORIGIN TIME - 0212Z 05 JUL 2008 COORDINATES - 53.8 NORTH 153.2 EAST DEPTH - 550 KM LOCATION - SEA OF OKHOTSK MAGNITUDE - 7.6

#### EVALUATION

A DESTRUCTIVE TSUNAMI WAS NOT GENERATED BASED ON EARTHQUAKE AND HISTORICAL TSUNAMI DATA.

THIS WILL BE THE ONLY BULLETIN ISSUED FOR THIS EVENT UNLESS ADDITIONAL INFORMATION BECOMES AVAILABLE.

THE JAPAN METEOROLOGICAL AGENCY MAY ALSO ISSUE TSUNAMI MESSAGES FOR THIS EVENT TO COUNTRIES IN THE NORTHWEST PACIFIC AND SOUTH CHINA SEA REGION. IN CASE OF CONFLICTING INFORMATION... THE MORE CONSERVATIVE INFORMATION SHOULD BE USED FOR SAFETY.

THE WEST COAST/ALASKA TSUNAMI WARNING CENTER WILL ISSUE PRODUCTS FOR ALASKA... BRITISH COLUMBIA...WASHINGTON...OREGON... CALIFORNIA.

#### **TSUNAMI WARNING**

The highest level of tsunami alert. Warnings are issued by the TWCs due to confirmation of a destructive tsunami wave or the threat of an imminent tsunami. Initially the warnings are based only on seismic information without tsunami confirmation as a means of providing the earliest possible alert to at-risk populations. Warnings initially place a restricted area in a condition that requires all coastal areas in the region to be prepared for imminent flooding. Subsequent text products are issued at least hourly or as conditions warrant to continue, expand, restrict, or end the warning. In the event a tsunami has been confirmed which could cause damage at distances greater than 1,000 km from the epicentre, the warning may be extended to a larger area.

#### **TSUNAMI WARNING CENTRE (TWC)**

Centre that issues timely tsunami information messages. The messages can be information, watch, or warning messages, and are based on the available seismological and sea level data as evaluated by the TWC, or on evaluations received by the TWC from other monitoring agencies. The messages are advisory to the official designated emergency response agencies. Regional TWCs monitor and provide tsunami information to Member States on potential ocean-wide tsunamis using global data networks, and can often issue messages within 10-20 minutes of the earthquake. Local TWCs monitor and provide tsunami information on potential local tsunamis that will strike within minutes. Local TWCs must have access to continuous, real-time, densely-spaced data



networks in order to characterize the earthquakes within seconds and issue a warning within minutes.

An example of a Regional Tsunami Warning Centre is the Pacific Tsunami Warning Center, which provides international tsunami warnings advisories to the Pacific. After the 26 December 2004 tsunami, the PTWC and JMA have acted as an Interim Regional TWC for the Indian Ocean.

Examples of sub-regional TWCs are the NWPTAC operated by the JMA of Japan, and the WC/ATWC operated by the US NOAA. In the Pacific, these centres, along with long-time national centres in Chile, France, and Russia, also act as national TWCs providing local tsunami warnings for their countries.

### **TSUNAMI WARNING CENTRE PRODUCTS**

Tsunami Warning Centres issue four basic types of messages: 1) information bulletins when a large earthquake has occurred but there is little or no tsunami threat; 2) local, regional, or oceanwide watch and warning bulletins when there is an imminent tsunami threat; 3) cancellation bulletins when destructive tsunami waves are gone; and 4) tsunami communication test messages to regularly exercise the system. Initial or local evaluations and messages are based only on the faster arriving seismic information, specifically earthquake location, magnitude, and depth. If a tsunami threat is large, estimated tsunami wave arrival times, and possibly wave height forecasts, are reported, and sea level records are examined to confirm tsunami generation. Watch and Warning Bulletins are updated regularly, or as needed, or cancelled when the threat is gone. In the Pacific, the types of messages issued by the PTWC include a Pacific-Wide Tsunami Warning Bulletin, Regional Expanding Tsunami Warning and Watch Bulletin, Regional Fixed Tsunami Warning Bulletin, Warning Cancellation Bulletin, Tsunami Information Bulletin, and Tsunami Communication Test Dummy Message.

### **T**SUNAMI WATCH

The second highest level of tsunami alert. Watches are issued by the Tsunami Warning Centres (TWCs) based on seismic information without destructive tsunami confirmation. The watch is issued as a means of alerting the affected populations located, for example, one to three hours tsunami travel time beyond the warned area. Subsequent text products are issued at least hourly to expand the watch and warning area, upgrade all areas to a warning, or cancel the watch and warning. A Tsunami Watch may be included in the text of the message that disseminates a Tsunami Warning.

### **UNESCO**

United Nations Educational, Scientific and Cultural Organization. Established in 1945, UNESCO promotes international cooperation among its Member States in the fields of education, science, culture and communication. Today, UNESCO works as a laboratory of ideas and standard setter to forge universal agreements on emerging ethical issues. The Organization also serves as a clearinghouse that disseminates and shares information and knowledge, while helping Member States to build their human and institutional capacities in diverse fields. The UNESCO Constitution states, "Since wars begin in the minds of men, it is the minds of men that the defenses of peace must be constructed." (http://www.unesco.org/)

### WDC

World Data Center. The WDC system was created to archive and distribute data collected from the observational programmes of the 1957-1958 International Geophysical Year. Originally established in the United States, Europe, Russia, and Japan, the WDC system has since expanded to other countries and to new scientific disciplines. The WDC system now includes 52 Centres in 12 countries. NGDC is co-located with the World Data Center for Geophysics and Marine Geology which combines the responsibilities of the former WDC-Marine Geology and Geophysics and WDC-Solid Earth Geophysics into a single new data center that manages global geophysical, sea floor, and natural hazards data. These data cover time scales ranging from seconds to millennia and they provide baseline information for research in many disciplines.

(http://www.ngdc.noaa.gov/wdc/wdcmain.html)





### GENERAL

Atwater, Brian F., et.al., Surviving a tsunami -Lessons from Chile, Hawaii, and Japan. USGS Circular 1187. [Washington DC]: GPO, rev 2005.

Bernard, E.N., ed., Developing tsunami-resilient communities: The National Tsunami Hazard Mitigation Program, Dorchedt: Springer, 2005.

Dudley, M. and M. Lee, Tsunami! 2<sup>nd</sup> Ed., Honolulu: University of Hawaii Press, 1998.

lida, K., Catalog of tsunamis in Japan and its neighboring countries. Special Report, Yashigasa, Yakusa-cho, Toyota-shi: Aichi Institute of Technology, 1984.

Tsunami Newsletter, IOC International Tsunami Information Centre, Honolulu, 1965 to present.

UNESCO-IOC. IUGG/IOC TIME Project: Numerical method of tsunami simulation with the leap-frog scheme. IOC Manuals and Guides No. 35. Paris, UNESCO, 1997.

UNESCO-IOC. Master plan for the Tsunami Warning System in the Pacific. Second Edition. IOC Information document No. 1124. Paris, UNESCO, 1999. *In English; Spanish, French and Russian version also online.* 

UNESCO-IOC International Tsunami Information Centre. Tsunami: The Great Waves. IOC Brochure 2006-2. Paris, UNESCO, 2005. In English; Spanish and French earlier version also online.

UNESCO-IOC International Tsunami Information Centre. Tsunami Glossary. IOC Information document No. 1221. Paris, UNESCO, 2006. *Earlier revision in Spanish and French.* 

UNESCO-IOC. Tsunami Glossary: A glossary of terms and acronyms used in the tsunami literature. IOC Technical Series No. 37. Paris, UNESCO, 1991.

UNESCO-IOC International Tsunami Information Centre. Tsunami Warning!, IOC Information Document No. 1223. Paris, UNESCO, 2005.

UNESCO-IOC. Post-tsunami survey field guide. First Edition. IOC Manuals and Guides No. 37. Paris, UNESCO, 1998. *Versions in Russian*, French and Spanish. English and Spanish versions available online through ITIC Web Site.

### **EVENT CATALOGUES**

Berninghausen, W.H., Tsunamis and seismic seiches of Southeast Asia. Bulletin of the Seismological Society of America, 59, 289-297, 1969.

Berninghausen, W.H., Tsunamis and seismic seiches reported from regions adjacent to the Indian Ocean. Bulletin of the Seismological Society of America, 56(1), 69-74, 1966.

Berninghausen, W.H., Tsunamis and seismic seiches reported from the Western North and Atlantic and the coastal waters of Northwestern Europe. Informal Report No. 68-05, Washington DC: Naval Oceanographic Office, 1968.

Berninghausen, W.H., Tsunamis reported from the west coast of South America, 1562-1960. Bull. Seismol. Soc. Amer., 52, 915-921, 1962.

Berninghausen, W. H., Tsunamis and seismic seiches reported from the eastern Atlantic south of the Bay of Biscay. Bull. Seismol. Soc. Amer., 54, 439-442, 1964.

Dunbar, P.K., P. A. Lockridge, and L. S. Whiteside, Catalogue of Significant Earthquakes 2150BC1991AD. US Department of Commerce, NOAA, National Geophysical Data Center, Boulder, USA, World Data Center A for Solid Earth Geophysics Reports SE-49, 320 pp, 1992.

Everingham, I.B., Preliminary Catalogue of Tsunamis for the New Guinea I Solomon Island Region 1768-1972. Bureau of Mineral Resources, Canberra, Australia, Report 180, 78 pp, 1977.

Heck, N.H., List of seismic sea waves. Bulletin of the Seismological Society of America, Vol. 37, No. 4, p. 269-286, 1947.

lida, K., D. Cox, and G. Pararas-Carayannis, Preliminary catalog of tsunamis occurring in the Pacific Ocean. Data Report No. 5, Hawaii Institute of Geophysics, HIG-67-10. Honolulu: University of Hawaii, re-issued 1972. URL: http://www.soest.hawaii.edu/Library/Tsunami%2 OReports/lida\_et\_al.pdf



Pararas-Carayannis, G., Catalogue of Tsunamis in the Hawaiian Islands. US Department of Commerce, NOAA National Geophysical Center, Boulder, USA, World Data Center A for Solid Earth Geophysics Publication, 94 pp, 1969.

Lander, J.F., Tsunamis Affecting Alaska 1737-1996. KGRD No. 31, National Oceanic and Atmospheric Administration, National Geophysical Data Center, Boulder, Colorado, USA, September, 155, 1996.

Lander, J.F, P.A. Lockridge, and M.J. Kozuch, Tsunamis affecting the West Coast of the United States 1806-1992. US Department of Commerce, NOAA, National Geophysical Data Center, Boulder, USA, NGDC Key to Geophysical Records Documentation KGRD-29. 242 pp, 1993.

Lander, J., and P. Lockridge, United States Tsunamis (including United States Possessions) 1690-1988. Publication 41-2, Boulder: National Geophysical Data Center, 1989.

Lockridge, P.A., Tsunamis in Peru-Chile, Report SE-39, World Data Center A for Solid Earth Geophysics, NOAA, National Geophysical Data Center, Boulder, CO, USA, 97, 1985.

Lockridge, P.A., L.S. Whiteside and J.F. Lander, Tsunamis and Tsunami-like Waves of the Eastern United States. Science of Tsunami Hazards, the International Journal of the Tsunami Society, Honolulu, Hawaii, USA, 20 (3), 120-144, 2002.

Lockridge, P.A. and R. H. Smith, 1984 : Map of Tsunamis in the Pacific Basin, 1900-1983. Scale 1:17,000,000. US NOAA National Geophysical Data Center World Data Centre A For Solid Earth Geophysics and Circum-Pacific Council for Energy and Minteralo Resources Map Project.

Molina, E.e (Seccion de Sismologia, INSIVUMEH, Guatemala). Tsunami catalogue for Central America 1539-1996 [Report]. Reduction of natural disasters in Central America. Universitas Bergensis Technical Report no. II 1-04, Bergen, Norway: Institute of Solid Earth Physics, University of Bergen; 1997.

Murty, T.S. and M. Rafiq, A tentative list of tsunamis in the marginal seas of the north Indian Ocean. Natural Hazards, 4 (1), 81-83, 1991.

O'Loughlin, K.F. and J.F. Lander, Caribbean tsunamis: A 500-year history from 1498-1998, Advances in Natural and Technological Hazards Research, Vol. 20 Boston, MA: Kluwer Academic Publishers, 2003.

Soloviev, S.L., et al., Tsunamis in the Mediterranean Sea 2000 BC-2000AD. Advances in Natural and Technological Hazards Research, Vol. 13, Dordrecht: Kluwer Academic Publishers, 2000.

Soloviev, S.L., and C. N. Go, A catalogue of tsunamis on the western shore of the Pacific Ocean. Academy of Sciences of the USSR, Nauka Publishing House, Moscow, 310 pp. *Canadian Translation of Fisheries and Aquatic Sciences No. 5077, 1984, translation available from Canada Institute for Scientific and Technical Information, National Research Council, Ottawa, Ontario, Canada K1AOS2, 447 pp, 1974.* 

Soloviev, S.L., and C. N. Go, A catalogue of tsunamis on the eastern shore of the Pacific Ocean. Academy of Sciences of the USSR, Nauka Publishing House, Moscow, 204 pp. *Canadian Translation of Fisheries and Aquatic Sciences No. 5078, 1984, translation available from Canada Institute for Scientific and Technical Information, National Research Council, Ottawa, Ontario, Canada K1AOS2, 293 pp, 1975.* 

Soloviev, S.L., C. Go, and C. S. Kim, Catalogue of Tsunamis in the Pacific 1969-1982, Results of Researches on the International Geophysical Projects. Moscow: Academy of Sciences of the USSR, 1992.

Soloviev, S.L. and M.D. Ferchev, Summary of Data on Tsunamis in the USSR. Bulletin of the Council for Seismology, Academy of Sciences of the USSR [Byulleten Soveta po Seismologii Akademiya Nauk, SSSR], 9, 23-55, Moscow, USSR, 37, 1961.

Tinti, S., A. Maramai and L. Graziani. A new version of the European Tsunami Catalogue: updating and revision. Natural Hazards and Earth System Sciences, 1, 1-8, 2001.

Tsunami Laboratory, ICMMG SD RAS, Novosibirsk, Russia, ITDB/WLD (2005) Integrated Tsunami Database for the World Ocean, Version 5.15 of July 31, 2005, CD-ROM.



### TECHNICAL

Abe, K., Size of great earthquakes 1837-1974 inferred from tsunami data, J. Geophys. Res, 84, 1561-1568, 1979.

Abe, Katsuyuki, A new scale of tsunami magnitude, Mt. in Tsunamis: Their science and engineering, lida and Iwasaki, eds., Tokyo: Terra Scientific Publishing Company, 91-101, 1983.

Ambraseys, N.N., Data for the investigation of the seismic sea-waves in the Eastern Mediterranean, Bulletin of the Seismological Society of America, 52:4, 895-913, 1962.

Dmowska, R. and B. Saltzman, eds., Tsunamigenic earthquakes and their consequences. Advances in Geophysics, Vol. 39, San Diego: Academic Press, 1998.

European Commission. Directorate General for Science, Research and Development, UNESCO and Commissariat à l'Energie Atomique (CEA), International Conference on Tsunamis, 26-28 May 1998. France: CEA, 1998.

Hatori, T., Relation between tsunami magnitude and wave energy, Bull. Earthquake Res. Inst. Univ. Tokyo, 54, 531-541, 1979. *In Japanese with English abstract.* 

Hatori, T., Classification of tsunami magnitude scale, Bull. Earthquake Res. Inst. Univ. Tokyo, 61, 503-515, 1986. *In Japanese with English abstract.* 

lida, K. and T. Iwasaki, eds., Tsunamis: Their science and engineering, Proceedings of the International Tsunami Symposium (1981), Tokyo: Terra Scientific, 1983.

Kanamori, H., "Mechanism of tsunami earthquakes," Phys. Earth Planet. Inter., 6, 346-359, 1972.

Keating, B., Waythomas, C., and A. Dawson, eds., Landslides and Tsunamis. Pageoph Topical Volumes, Basel: Birhäuser Verlag, 2000.

Mader, C., Numerical modeling of water waves, 2<sup>nd</sup> ed. Boca Raton, FL: CRC Press, 2004.

Papadopoulus, G., and F. Imamura, "A proposal for a new tsunami intensity scale," International Tsunami Symposium Proceedings, Session 5, Number 5-1, Seattle, 2001.

Satake, K., ed., Tsunamis: Case studies and recent developments. Dordrecht: Springer, 2005.

Satake, K. and F. Imamura, eds., Tsunamis 1992-1994: Their generation, dynamics, and hazard, Pageoph Topical Volumes. Basel: Birhäuser Verlag, 1995.

Sauber, J. and R. Dmowska, Seismogenic and tsunamigenic processes in shallow subduction zones. Pageoph Topical Volumes. Basel: Birhäuser Verlag, 1999.

Shuto, N., "Tsunami intensity and disasters," in Tsunamis in the World, S. Tinti, ed., Dordrecht: Kluwer Academic Publishers, 197-216, 1993.

Sieberg, A., Erdbebenkunde, Jena: Fischer, 102-104, 1923. *Sieberg's scale.* 

Soloviev, S.L., "Recurrence of earthquakes and tsunamis in the Pacific Ocean," in Tsunamis in the Pacific Ocean, edited by W. M. Adams, Honolulu: East-West Center Press, 149-164, 1970.

Soloviev, S.L., "Recurrence of earthquakes and tsunamis in the Pacific Ocean," Volny Tsunami (Trudy SahkNII, Issue 29), Yuzhno-Sakhalinsk, 7-46, 1972. *In Russian.* 

Tinti, S., ed., Tsunamis in the World : Fifteenth International Tsunami Symposium, 1991, Advances in Natural and Technological Hazards Research, Vol. 1. Dordrecht: Kluwer Academic Publishers, 1993.

Tsuchiya, Y. and N. Shuto, eds., Tsunami: Progress in prediction, disaster prevention and warning. Advances in Natural and Technological Hazards Research, Vol. 4. Dordrecht: Kluwer Academic Publishers, 1995.

Yeh, H., Liu, P., and C. Synolakis, Long-wave runup models, Singapore: World Scientific, 1996.

### **TEXTBOOKS AND TEACHERS**

### **GUIDEBOOKS (in English and Spanish)**

Pre-elementary school: Earthquakes and tsunamis Chile: SHOA/IOC/ITIC, 1996. Revised 2003 in Spanish.

2-4 Grade: I invite you to know the earth I. Chile: SHOA/IOC/ITIC, 1997.

5-8 Grade: I invite you to know the earth II. Chile: SHOA/IOC/ITIC, 1997.

High School: Earthquakes and tsunamis. Chile: SHOA/IOC/ITIC, 1997.



Arrival time	16
Breaker	7
Breakwater	7
Cable ocean-bottom instrument	21
Cotidal	21
Crest length	16
Deep-ocean tsunami detection	21
system (DART®)	
Drop	16
Eddy	7
	16
Elapsed time	
Estimated time of arrival (ETA)	8
Evacuation map	8
Forecast Point	24
GLOOS	24
GOOS	24
GTS	24
Historical tsunami	2
Historical tsunami data	8
ICG	24
ICG/CARIBE-EWS	24
ICG/IOTWS	25
ICG/ITSU	25
ICG/NEAMTWS	25
ICG/PTWS	25
ICG Tsunami National	25
Contact (TNC)	25
ICG Tsunami Warning	25
	20
Focal Point (TWFP)	4.0
Initial rise	16
Intensity	16
Inundation or Inundation-distance	16
Inundation (maximum)	16
Inundation area	16
Inundation line	17
IOC	25
ITIC	25
IUGG	26
JMA	26
Leading wave	17
Localtsunami	2
Low water	21
Magnitude	17
Maremoto	2
Mareogram	21
maroogram	

Mareograph	2
Marigram	2
Master Plan	2 2
Mean height	1
Mean sea level	2
Meteorological tsunami	_
(meteotsunami)	
Microtsunami	
Ocean-wide tsunami	
Ocean-wide tsunami warning	2
0	2
Operational Users Guide	2
for the Tsunami Warning System	
Overflow	1
Paleotsunami	
Post-tsunami survey	1
Probable maximum water level	2
PTWC and WC/ATWC	2
Recession	1
Reference sea level	2
Refraction diagrams	2 2 1 2 2 2 2
Regional Expanding Tsunami	2
Watch/Warning Bulletin (RWW)	
Regional Fixed Tsunami	2
Warning Bulletin	
Regional tsunami	
Rise	1
Runup	1
Runup distribution	1
Sealevel	2
Sea level station	2
Seiche	
Seismic sea wave	
Sieberg tsunami intensity scale	1
Significant wave height	1
Spreading	1
Subsidence (uplift)	1
Teletsunami or Distant tsunami	
Tidal wave	2
Tide	2
	2
Tide amplitude	2
Tide gauge	2 2 2 2
Tide station	2
Traveltime	
Travel time map	~
Tsunameter	2

22	Tsunami	6
21	Tsunami amplitude	19
26	Tsunami bore	9
17	Tsunami Bulletin Board (TBB)	30
22	Tsunami damage	9
2	Tsunami dispersion	10
	Tsunami earthquake	6
2	Tsunami edge wave	10
2	Tsunami Emergency	31
26	Response (TER)	
27	Tsunami forerunner	10
	Tsunami generation	10
17	Tsunami generation theory	11
2	Tsunami hazard	11
17	Tsunami hazard assessment	11
22	Tsunami impact	11
27	Tsunami Information Bulletin (TIB)	31
18	Tsunami intensity	20
22	Tsunami magnitude	20
22	Tsunami numerical modelling	12
28	Tsunami observation	13
20	Tsunami period	20
29	Tsunami period (dominant)	20
4	Tsunami preparedness	13
4 18	Tsunami propagation	14 15
18	Tsunami resonance Tsunami risk	15
18	Tsunami sediments	6
22	Tsunami simulation	15
22	Tsunami source	15
8	Tsunami velocity or Shallow water	15
8	velocity	10
18	Tsunami Warning	31
19	Tsunami Warning Centre (TWC)	31
19	Tsunami Warning Centre Products	32
19	Tsunami Watch	32
5	Tsunami wave length	20
23	Tsunami zonation	15
23	Tsunamic	15
23	Tsunamigenic	15
23	UNESCO	32
23	Water level (maximum)	20
8	Wave crest	20
8	Wave trough	20
22	WDC	32



#### THE INTERNATIONAL TSUNAMI INFORMATION CENTER (ITIC)

A UNESCO/IOC - NOAA Partnership

737 Bishop Street, Suite 2200 Honolulu, Hawaii 96813-3213, U.S.A. http://www.tsunamiwave.info

Tel: <1> 808-532-6422 Fax: <1> 808-532-5576 E-mail: itic.tsunami@unesco.org

Located in Honolulu, The International Tsunami Information Center (ITIC) was established on 12 November 1965 by the Intergovernmental Oceanographic Commission (IOC) of the United Nations Educational, Scientific, and Cultural Organization (UNESCO). The first session of the International Coordination Group for the Tsunami Warning System in the Pacific (ITSU) convened in 1968. In 2005, the ITSU was renamed as the Intergovernmental Coordination Group for the Pacific Tsunami Warning and Mitigation System (ICG/PTWS) to emphasize the comprehensive nature of risk reduction.

The ITIC thanks the following scientists for their review assistance: Paula Dunbar, Fumihiko Imamura, Osamu Kamigaichi, Emilio Lorca, Charles McCreery, Modesto Ortiz, William Power, Alexander Rabinovich, Kenji Satake, François Schindele, Fred Stephenson, Costas Synolakis, and Masahiro Yamamoto.

International Tsunami (ITSU) wave courtesy of Aqualog, France.



# Intergovernmental Oceanographic Commission Technical series

Andrew I was



8